

Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2 (375 EUR)



Locatie **Flevoland, Almere**
<https://www.advertentiex.nl/x-1176575-z>

T112D2

Size: 12"



Power Handling (Watts RMS): 600 Watts RMS
1200 Watts Max

Nominal Impedance: Dual 2-Ohm

Voice Coil Diameter: 3" anodized aluminum

Magnet Weight (oz): 124 oz. double stacked

Sneaker Connector: Dual 8 AWG slot load

 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2	 https://www.advertentiex.nl/x-1176575-z Rockford Fosgate T1 12D2 Subwoofer en Versterker T400-2
--	---	---	---	--	---	---	---	---	---

Qms: 4.46

Qes: 0.53

Qts: 0.47

Vas (Liters): 34.8

Sd (cm²): 460

SPL (dB @ 1w/1m): 86

Xmax (mm): 14

Woofers Displacement: 0.08 cu. ft.
(2.26 Liters)

Cutout Diameter: 10.8125 in.
(27.46 cm)

Mounting Depth: 6.625 in.
(16.83 cm)

Shipping Weight: 30.6 Lbs.
(13.9 Kg.)

T400.2

Number of Channels 2

Rated Power

continuous power 120W x 2 @ 4-Ohms RMS

200W x 2 @ 2-Ohms RMS

400W x 1 @ 4-Ohms bridged RMS

2-Ohms x 1 bridged Stable

Total Power

total sum of 'rated power'; 400 Watts

Dynamic Power

powercube measurement (info) 145 Watts x 2 @ 4-Ohms 0° Res

243 Watts x 2 @ 2-Ohms 0° Res

Bridgeable Yes

Efficiency (average) 76% @ 4-Ohm

71% @ 2-Ohm

Crossover Controls High-Pass (HP): 50-500Hz 24dB/octave Butterworth

Low-Pass (LP): 50-500Hz 24dB/octave Butterworth

Tone Controls Treble: 0dB to +12dB @ 12kHz

Bass: 0dB to +18dB @ 45Hz

Signal Input Low level: 1 RCA pair

Signal Output Low level: 1 RCA pair

Power Input Connector Block

Power Wire Gauge 4 AWG

Speaker Output Connector Screw terminal barrier strip

Speaker Wire Gauge 8 AWG to 18 AWG

Heat Sink Type Cast aluminum

Cooling Convection

Remote Controls Optional Remote Punch EQ

(overrides built-in Punch EQ)

Visual Indicators Power

Thermal

Protect

Circuit Topology Class Class A/B

Frequency Response 20Hz to 20kHz +/- 1dB

Shipping Weight 10.29 Lbs.

(4.66 Kg.)

Dimensions (HxWxL) 2.14 x 8.14 x 11.41 (in)

5.42 x 20.68 x 28.97 (cm)

LET OP: BIEDEN VANAF 375,- ALS SET.....

LOS SUBWOOFER 200,- VERSTERKER 200,-

IS SPELENDE TE BELUISTEREN IN MIJN AUTO

inbouw mogelijk bij cardeluxe almere

Wat je op de foto zietIs wat je krijgt !!!

Doe een goed bodwel serieus bieden...en het kan snel van jou zijn....

Voor meer info kan je mailen of bellen (a.u.b. Niet naar 22 uur bellen .

KIJK OOK MIJN ANDERE!!