

ADSL2 modem router Zyxel P-2602-H



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentieX.nl/x-505604-z>



Te koop ADSL2+ modem router Zyxel P-2602-H.

Specificaties:

DSL Features:

Support Multi-Mode Standard (ANSI T1.413, Issue 2 ; G.dmt(G.992.1); G.lite(G.992.2)).

ADSL2 G.dmt.bis (G.992.3)

ADSL2 G.lite.bis (G.992.4)

ADSL2+ (G.992.5)

Reach Extended ADSL (RE ADSL)

ADSL Physical Connection ATM AAL5 (ATM Adaptation Layer Type 5)

Support PPP over ATM AAL5 (RFC2364)

PPP over Ethernet (RFC 2516)

Support VC-based and LLC-based Multiplexing

Support up to 8 PVCs

F4/F5 OAM

Zero Configuration

Annex M

Router Features

NAT (Including Multi-to-multi NAT) / SUA, 1024 NAT Sessions, 512 Per Host

NAT Server (Port Forwarding)

Static NAT Server
 Dynamic NAT Support
 IP Multicasting, IGMP V1 and V2

Dynamic DNS Support

IP Alias
 Voice Functionality
 SIP (RFC 3361) v2
 SIP (RFC 3327)
 RTP (RFC 3389)



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>




ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>



ADSL2 modem router Zyxel
 P-2602-H

<https://www.advertentieX.nl/x-505604-z>

RTCP (RFC 1890)
Echo Cancellation: G.168
Voice Activity Detection (VAD)
Silence Suppression
Comfort Noise Generation (CNG)
Support TOS & Diffserv Tagging
VLAN Tag Support
Codec: G.711 (PCM A-law or -law selectable), G.729a/b
Option: G.726 (ADPCM), G.723*
DTMF Detection
Multiple SIP Number Supports
Multiple Channel Supports
Modem and Fax Tone Detection
T.38 Fax Relay
Polarity Reverse*
DNS SRV*
Phone Features
Call Waiting (CW)
Call Waiting w/ Caller ID
Call Forwarding (Unconditional/Busy/No Answer)
Call Transferring
Three Way Conference with Local Mixing
Calling Line Identification Presentation (CLIP)
Calling Line Identification Restriction (CLIR)
Call Hold / Call Retrieve
Incoming Call Policy (Call Accept/Call Forward/Call Block)
Second Call
Internal Call
Early Media
Flash Hook Timer
Music on Hold
Message Waiting Indicator (MWI) (RFC 3842)
Interactive Voice Response (IVR)
Speed Dial (Phone Book)
Do Not Disturb (DND)*
Malicious Call Identification (MCID)*
Call Block*
Distinctive Ringing*
Last Number Redial*
Connected Line Identification Presentation (COLP)*

Connected Line Identification Restriction (COLR)*
Call Filtering*
Automatic Call Return*
MWI by E-mail*
Fixed Destination Call*
Network Functionality
Friendly Web-based Configuration Tool
SNMP v1 & v2 with MIB II
Remote FTP/TFTP Firmware Upgrade and Configuration Backup/ Restore
Secure TFTP and HTTP Auto-provisioning (Default by 3DES Encryption)
IVR for IP Address and FW Upgrade
2-tier Web and Management: Admin & Guest Access Authority (by project)
Remote Management Control: Telnet, FTP, Web
Easy Provisioning Management of TR-069 and TR-104*
IP Management
SUA/NAT Internet Sharing
Multimedia Applications Pass-through NAT
DHCP Server/Client/Relay
DNS Proxy
UPnP Support
Firewall Security
ICSA certified firewall with Stateful Packet Inspection
Prevent DoS Attack
Access Control of Service
Content Filtering: URL Blocking such as ActiveX, Java, Cookies and Web
IP & Generic Packet Filtering
Real-time Attack Alert and Log
Virtual Private Network
5 IPSec VPN Tunnels (2 Concurrent VPN Tunnels)
IKE and Manual Key Management
AH and ESP Protocol
DES/3DES and AES Encryption (S/W)
SHA-1 and MD5 Authentication
Tunnel and Transport Mode Encapsulation
IPSec NAT Traversal
NETBIOS Pass-through for IPSec
Hardware Specification

RJ-11 DSL port for ADSL Annex A and R-J45 DSL Port for ADSL Annex B and U-R2.
4-port Auto MDI/MDI-X 10/100M Ethernet port.

Restore Factory Default Button

2 FXS POTS Interface

Physical Specifications

Item weight: 600 g (1.32 lb)

Item dimensions (WxDxH):165 x 65 x 242 mm (6.50" x 2.56" x 9.53")

Environmental Specifications

Operating Environment

Temperature: 0 to 40 (32°F to 104°F)

Humidity: 20% to 95% RH

Storage Environment

Temperature: -30 to 60 (-22°F to 140°F)

Humidity: 20% to 95%

0646132783