

SUPERMICRO SYS-5046A-XB Intel Xeon Server (300 EUR)



Locatie: Noord-Holland, Amsterdam
<https://www.advertentieX.nl/x-748171-z>

SUPERMICRO SYS-5046A-XB

Merk: Supermicro
 Series: SuperWorkstation
 Model: SYS-5046A-XB

CPU Support:








CPU type: Intel Core i7 990X, i7-980X, i7-975 and i7-965 Extreme EditionIntel Core i7 seriesIntel Xeon 5600/5500 seriesIntel Xeon 3600/3500 series

CPU Socket: LGA 1366
 Geïnstalleerde CPU: Geen CPU geïnstalleerd
 Maximale processoren: 1

Chipset:

North bridge: Intel x58
 South bridge: ICH10R

Memory Supported:

 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel	 Memory Supported: 24GB Installed: 24GB Max Memory: 24GB Memory Type: DDR3 Channel Supported: Triple Channel
---	--	--	--	---	--	--	--	--	--

PCI: 1

Audio:OnboardAudio: Realtek ALC883 7.1 HD audio

Communications:FirstLAN: Intel 82574L

Second LAN: Intel 82574L

Max. LAN Speed: Dual 10/100/1000Mbps

Expansion Bays:

5.25" Bays:

2x 5.25" Peripheral Drive Bay

1x 5.25" Bay For Floppy Drive

Host-Swap Bays: 6x SATA Hot-swap Drives

2x Spare Trays

Panel Ports:

Front USB: 2

PS/2: 2

Rear USB: 8

RJ45: 2

Rear Audio Ports:

6x analog outputs

1x S/PDIF digital output

Power Supply:Max.Power: 865W AC power supply (cooling-redundant) w/ PFC

Features:Color:black

Processor: IntelCore i7-980X, i7-975 and i7-965 Extreme EditionIntelCore i7 seriesIntelXeon 5600/5500 seriesIntelXeon 3600/3500 series QPI(up to 6.4

GT/s)Buttons:Power On/Off, System ResetLEDs:PowerLEDHarddrive activity LED2xNetwork activity LEDsSystemOverheat / Fan Fail LEDSC743SATA Backplane w/

Enclosure Management Fans:2x8cm Hot-swappable PWM Cooling Fans1x9cm Hot-Swappable Rear Exhaust PWM Fan1xActive heatsink w/ heatpipe. Supports nVidia

SLI and ATI CrossfireX Technology. Other:Chassis intrusion detection, Chassis intrusion header

Details: Form Factor: 4U Rackmountable / Tower

Dimensions & Weight:

Dimensions: 25.5" x17.2" x 7.0"

Weight: 63 lbs.