

# Cisco SF300-48P 48-Port 10100 PoE Managed Switch (450 EUR)



Locatie **Noord-Holland, Wervershoof**  
<https://www.advertentieX.nl/x-1136696-z>

Cisco SF300-48P 48-Port 10/100 PoE Managed Switch with Gigabit Uplinks

Rack-Mount 23 in. (58.4 cm) EIA  
 Included  
 Jumbo Frame Support  
 10 KB  
 Routing Protocol  
 Static IPv4 routing  
 Minimum Storage Temperature  
 -4 F  
 Depth  
 13.8 inches  
 MTBF  
 182,540 hour(s)  
 Cables Included  
 1x Serial Cable  
 Capacity  
 4K Active VLANs  
 Height  
 1.5 inches

Maximum Operating Temperature

Maximum Storage Temperature

Maximum Storage Temperature

Chinese (simplified), English, German, French, Italian, Spanish, Japanese

Width

13.8 inches

Enclosure Type

Desktop, rack-mountable - 1U

Maximum Storage Temperature

18 F

Maximum Storage Temperature

Maximum Storage Temperature

Maximum Storage Temperature


Maximum Storage Temperature

Maximum Storage Temperature

Maximum Storage Temperature



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch




Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch



Cisco SF300-48P 48-Port  
 10100 PoE Managed Switch

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

<https://www.advertentieX.nl/x-1136696-z>

---

Ports  
48 x 10/100 + 2 x combo Gigabit SFP + 2 x 10/100/1000

Device Type  
Switch - 48 ports - L3 - managed

Humidity Operating Range  
10-90% (non-condensing)

Weight  
13 lbs

Minimum Operating Temperature  
32 F

Interfaces  
48 x 10Base-T/100Base-TX - RJ-45 - PoE; 1 x console - 9 pin D-Sub (DB-9) - management; 4 x 10Base-T/100Base-TX/1000Base-T - RJ-45; 2 x SFP (mini-GBIC)

Humidity Storage Range  
10-90% (non-condensing)

Flash Memory  
16 MB

Voltage Required  
AC 120/230 V ( 50/60 Hz )

Performance  
Switching capacity: 17.6 Gbps; Forwarding performance (64-byte packet size): 13.1 Mpps

Power Device  
Power adapter - external

Power Over Ethernet (PoE)  
PoE

Status Indicators  
Link activity, port transmission speed, system

Ram  
128 MB

Authentication Method  
Secure Shell (SSH), RADIUS, +