

MacBook Pro 15034 mid 2010 (250 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiex.nl/x-1168609-z>

In uitstekende staat verkerende MB Pro 15" uit 2010.
Alles werkt nog uitstekend, heeft lichte gebruikssporen.
Recentelijk fans en batterij vervangen.

Gedetailleerde informatie:

Camera:

Built-in iSight:

Model ID: UVC Camera VendorID_1452 ProductID_34055
Unique ID: 0xfd1100005ac8507

Card Reader:

Built in SD Card Reader:

Vendor ID: 0x05ac
Product ID: 0x8403
Revision: 1.00

Serial Number: 9833



Background information



Model information:

Serial Number: D861015004NDGDL31

Manufacturer: SM


Device Name: A132

Pack Lot Code: 0

PCB Lot Code: 0

Firmware Version: 2

Hardware Revision: 00aa

 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010	 https://www.advertentex.nl/x-1168-609-z MacBook Pro 15034 mid 2010
--	---	---	---	--	---	---	---	---	---

Cell Revision: 2
Charge Information:
Charge Remaining (mAh): 5099
Fully Charged: No
Charging: No
Full Charge Capacity (mAh): 5712
Health Information:
Cycle Count: 3
Condition: Normal
Battery Installed: Yes
Amperage (mA): -2663
Voltage (mV): 11206

Diagnostics:

Power On Self-Test:

Last Run: 30/04/2021, 09:34
Result: Passed

Disc Burning:

MATSHITA DVD-R UJ-898:

Firmware Revision: HD10
Interconnect: ATAPI
Burn Support: Yes (Apple Shipping Drive)
Cache: 1024 KB
Reads DVD: Yes
CD-Write: -R, -RW
DVD-Write: -R, -R DL, -RW, +R, +R DL, +RW
Write Strategies: CD-TAO, CD-SAO, DVD-DAO
Media: To show the available burn speeds, insert a disc and choose File > Refresh Information

Ethernet Cards:

Broadcom 5764-B0:

Name: ethernet
Type: Ethernet Controller

Bus: PCI
Vendor ID: 0x14e4
Device ID: 0x1684
Subsystem Vendor ID: 0x14e4
Subsystem ID: 0x1684
Revision ID: 0x0010
Link Width: x1
BSD name: en0
Kext name: AppleBCM5701Ethernet.kext
Firmware version: 5764m-v3.38
Location:
/System/Library/Extensions/IONetworkingFamily.kext/Contents/PlugIns/AppleBCM5701Ethernet.kext
mDNS offload capable: c8:bc:c8:97:b7:88
Version: 10.3.5

FireWire:

FireWire Bus:

Maximum Speed: Up to 800 Mb/sec

Graphics/Displays:

Intel HD Graphics:

Chipset Model: Intel HD Graphics
Type: GPU
Bus: Built-In
VRAM (Dynamic, Max): 288 MB
Vendor: Intel
Device ID: 0x0046
Revision ID: 0x0018
Automatic Graphics Switching: Supported
gMux Version: 1.9.21
Displays:
Color LCD:
Display Type: LCD
Resolution: 1680 x 1050 (Widescreen Super eXtended Graphics Array Plus)
UI Looks like: 1680 x 1050
Framebuffer Depth: 24-Bit Color (ARGB8888)

Main Display: Yes
Mirror: Off
Online: Yes
Automatically Adjust Brightness: No
Connection Type: Internal

NVIDIA GeForce GT 330M:

Chipset Model: NVIDIA GeForce GT 330M
Type: GPU
Bus: PCIe
PCIe Lane Width: x16
VRAM (Total): 256 MB
Vendor: NVIDIA (0x10de)
Device ID: 0x0a29
Revision ID: 0x00a2
ROM Revision: 3560
Automatic Graphics Switching: Supported
gMux Version: 1.9.21

Hardware:

Hardware Overview:

Model Name: MacBook Pro
Model Identifier: MacBookPro6,2
Processor Name: Dual-Core Intel Core i5
Processor Speed: 2,4 GHz
Number of Processors: 1
Total Number of Cores: 2
L2 Cache (per Core): 256 KB
L3 Cache: 3 MB
Hyper-Threading Technology: Enabled
Memory: 8 GB
Boot ROM Version: 99.0.0.0.0
SMC Version (system): 1.58f16
Sudden Motion Sensor:
State: Enabled

Memory:

Memory Slots:

ECC: Disabled

Upgradeable Memory: Yes

BANK 0/DIMM0:

Size: 4 GB

Type: DDR3

Speed: 1067 MHz

Status: OK

Manufacturer: 0x802C

Part Number: 0x31364A5353353132363448592D3147314131

BANK 1/DIMM0:

Size: 4 GB

Type: DDR3

Speed: 1067 MHz

Status: OK

Manufacturer: 0x802C

Part Number: 0x31364A5353353132363448592D3147314131

Network:

Ethernet:

Type: Ethernet

Hardware: Ethernet

BSD Device Name: en0

Service Order: 0

FireWire:

Type: FireWire

Hardware: FireWire

BSD Device Name: fw0

Service Order: 1

Wi-Fi:

Type: AirPort
Hardware: AirPort
BSD Device Name: en1
Service Order: 2

Bluetooth PAN:

Type: Ethernet
Hardware: Ethernet
BSD Device Name: en2
Service Order: 3

SATA/SATA Express:

Intel 5 Series Chipset:

Vendor: Intel
Product: 5 Series Chipset
Link Speed: 3 Gigabit
Negotiated Link Speed: 3 Gigabit
Physical Interconnect: SATA
Description: AHCI Version 1.30 Supported

M4-CT512M4SSD2:

Capacity: 512,11 GB (512.110.190.592 bytes)
Model: M4-CT512M4SSD2
Revision: 040H
Native Command Queuing: Yes
Queue Depth: 32
Removable Media: No
Detachable Drive: No
BSD Name: disk0
Medium Type: Solid State
TRIM Support: Yes
Partition Map Type: GPT (GUID Partition Table)
S.M.A.R.T. status: Verified

Intel 5 Series Chipset:

Vendor: Intel
Product: 5 Series Chipset
Link Speed: 3 Gigabit
Negotiated Link Speed: 1.5 Gigabit
Physical Interconnect: SATA
Description: AHCI Version 1.30 Supported

MATSHITADVD-R UJ-898:

Model: MATSHITADVD-R UJ-898
Revision: HD10
Native Command Queuing: No
Detachable Drive: No
Power Off: Yes
Async Notification: No

Software:

System Software Overview:

System Version: macOS 10.15.7 (19H2)
Kernel Version: Darwin 19.6.0
Time since boot: 2:40

Wi-Fi:

Interfaces:

en1:

Card Type: AirPort Extreme (0x14E4, 0x93)
Firmware Version: Broadcom BCM43xx 1.0 (5.106.98.102.31)
MAC Address: 58:b0:35:84:60:bd
Locale: ETSI
Country Code: EU
Supported PHY Modes: 802.11 a/b/g/n
Supported Channels: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 36, 40, 44, 48
Wake On Wireless: Supported
Status: