

Cisco ASA 5505 series Firewall (45 EUR)



Locatie **Drenthe, Hoogeveen**
<https://www.advertentieX.nl/x-1197745-z>

(Refurbished)Cisco ASA 5505 series Firewall

3 Maanden garantie aanwezig.







Serial ports
 1 RJ-45 console

Non-Operating Relative Humidity
 5 to 95 percent noncondensing

Integrated I/O
 8-port FE with 2 Power over Ethernet (PoE) ports

Memory
 512 MB

Operating Relative Humidity
 5 to 95 percent noncondensing
 Non-Operating Altitude

 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z	 Cisco ASA 5505 series Firewall https://www.advertentieX.nl/x-1197745-z
---	--	--	--	---	--	--	--	--	--

Non-Operating Vibration
0.41 Grms2 (3 to 500 Hz) random input

Operating Shock
1.14 m/sec (45 in./sec) 1/2 sine input

Operating Acoustic Noise
60 dBa max

Integrated ports
8 port 10/100 switch with 2 Power over Ethernet ports

Input (per power supply) AC Range line voltage
100 to 240 VAC

Maximum 3DES/AES VPN throughput
100 Mbps

Maximum site-to-site and IPsec IKEv1 client VPN user sessions
10/25

Input (per power supply) AC Normal line voltage
100 to 240 VAC

Operating Altitude
Designed and tested for 0 to 9840 ft (3000 m); agency approved for 2000 m

Maximum Cisco AnyConnect IKEv2 remote access VPN or clientless VPN user sessions
25

Input (per power supply) AC Frequency
50/60 Hz

USB 2.0 ports
3 (1 front, 2 rear)

Form factor
Desktop

Non-Operating Temperature
-13 to 158 F (-25 to 70 C)

Output Steady State
20W

Input (per power supply) Dual-power supplies
None

Expansion slot
1 SSC

System bus
Multibus architecture

Packets per second (64 byte)
85000

Operating Vibration
0.41 Grms2 (3 to 500 Hz) random input

Input (per power supply) AC Current
1.8A

Weight
4.0 lb (1.8 kg) with AC power supply

IPS throughput
Up to 75 Mbps with AIP-SSC-5

VLANs
3 (trunking disabled) / 20 (trunking enabled)

Maximum new connections per second
5000

Operating Temperature
32 to 104 F (0 to 40 C)

New connections per second

4000

Stateful inspection throughput (max)
Up to 150 Mbps

Output Maximum Peak
96W

Non-Operating Shock
30G

Output heat dissipation
72 BTU/hr

Minimum system flash
128 MB

Power
AC/DC

Maximum concurrent sessions
10,000 / 25,000

Zie ook andere advertenties van PaterICT voor mooie