

Cisco ASA 5506-X Firewall (200 EUR)



Locatie **Drenthe, Hoogeveen**
<https://www.advertentieX.nl/x-1197746-z>

(Refurbished)Cisco ASA 5506-X Firewall

3 Maanden garantie aanwezig.

Serial ports
 1 RJ-45 and Mini USB console



Integrated I/O
 8 x 1 Gigabit Ethernet (GE)

Memory
 4 GB

Number of URLs categorized
 More than 280 million

Dual power supplies
 Not available

High-availability support

 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall	 https://www.advertentieX.nl/x-1197746-z Cisco ASA 5506-X Firewall
--	---	---	---	--	---	---	---	---	---

250 Mbps

Maximum 3DES/AES VPN throughput
100 Mbps

Maximum site-to-site and IPsec IKEv1 client VPN user sessions
10 / 50

Centralized configuration, logging, monitoring, and reporting
Multidevice Cisco Security Manager
Cisco FireSIGHT Management Center

Output steady state
12V @ 2.5 A

Maximum Cisco AnyConnect IKEv2 remote access VPN or clientless VPN user sessions
2 / 50

Solid-state drive
50 GB mSata

Form factor
Desktop, rack mountable

Maximum AVC and IPS throughput
125 Mbps

Maximum application control (AVC) throughput
250 Mbps

Packets per second (64 byte)
246,900

Maximum heat dissipation
103 BTU/hr

Weight
4 lb (1.82 kg) with AC power supply

VLANs

Maximum new connections per second
5,000

Dedicated management port
Yes (To be shared with with FirePOWER Services), 10/100/1000

Stateful inspection throughput (max)
750 Mbps

Output Maximum Peak
12V @ 5A

USB 2.0 Ports
USB port type A
High Speed 2.0

URL categories
80+

Minimum system flash
8 GB

Stateful inspection throughput (multiprotocol)
300 Mbps

Supported applications
More than 3000

AVC or IPS sizing throughput (440-byte HTTP)
90 Mbps

Maximum concurrent sessions
20,000; 50,000

Zie ook andere advertenties van PaterICT voor mooie