

ROCKFORD FOSGATE T400-4 VERSTERKER Nieuwprijs 480 (200 EUR)



Locatie **Flevoland, Almere**
<https://www.advertentiax.nl/x-1200005-z>

Number of Channels , 4
 Rated Power
 continuous power ,
 60W x 4 @ 4-Ohms RMS
 100W x 4 @ 2-Ohms RMS
 200W x 2 @ 4-Ohms bridged RMS
 2-Ohms x 2 bridged Stable
 Total Power
 total sum of rated power , 400 Watts
 Dynamic Power
 powercube measurement (info) , Front Channels
 90 Watts x 2 @ 4-Ohms 0° Res
 154 Watts x 2 @ 2-Ohms 0° Res
 Rear Channels
 90 Watts x 2 @ 4-Ohms 0° Res
 154 Watts x 2 @ 2-Ohms 0° Res
 Bridgeable , Yes
 Efficiency (average) , 69% @ 4-Ohm
 68% @ 2-Ohm
 Crossover Controls , Front High-Pass (HP): 50-500Hz 24dB/octave Butterworth

Front Low-Pass (LP): 50-500Hz 24dB/octave Butterworth
 Rear Low-Pass (LP): 50-500Hz 24dB/octave Butterworth
 Front High-Pass (HP): 50-500Hz 24dB/octave Butterworth
 Rear High-Pass (HP): 50-500Hz 24dB/octave Butterworth
 Bass: 0dB to +12dB @ 45Hz
 Treble: 0dB to +12dB @ 12kHz
 Signal Input: Front Low level: RCA pair
 Signal Output , n/a



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>




ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>



ROCKFORD FOSGATE
 T400-4 VERSTERKER
 Nieuwprijs 480
<https://www.advertentiax.nl/x-1200005-z>

Power Input Connector , Block
Power Wire Gauge , 4 AWG
Speaker Output Connector , Screw terminal barrier strip
Speaker Wire Gauge , 8 AWG to 18 AWG
Heat Sink Type , Cast aluminum
Cooling , Convection
Remote Controls , Optional Remote Punch EQ
(overrides rear channel built-in Punch EQ)
Visual Indicators , Power
Thermal
Protect
Circuit Topology Class , Class A/B
Frequency Response , 20Hz to 20kHz +/- 1dB
Shipping Weight , 11.90 Lbs.
(5.39 Kg.)
Dimensions (HxWxL) , 2.14 x 8.14 x 13.66 (in)
5.42 x 20.68 x 34.69 (cm)

LET OP: BIEDEN VANAF 175,- NIEUWPRIJS NOG STEEDS 480,-

IS SPELENDE TE BELUISTEREN IN MIJN AUTO

inbouw mogelijk bij cardeluxe almere

Wat je op de foto zietIs wat je krijgt !!!
Doe een goed bodwel serieus bieden...en hij kan snel van jou zijn
Verzenden kan ook.....Verzendkosten en risico voor de koper !!!
Voor meer info kan je mailen of bellen (a.u.b. Niet naar 22 uur bellen .

KIJK OOK MIJN ANDERE!!!