

nieuw AudioSystem Italy 10-kanaals DSP versterker (469 EUR)



Locatie **Noord-Brabant, Etten-Leur**
<https://www.advertentiax.nl/x-1243008-z>

8-kanaals (+2) versterker met geïntegreerde Digital Sound Processor.

469,- euro

Ideaal voor volledig digitaal aansturen van actieve speakersets of OEM installatie zoals vw/audio/bmw/mercedes

Optionele remote controller (DRC)

Output: 8x80Watt RMS @ 4Ohm
 & 2 processed RCA uitgangen voor externe (subwoofer)versterker.

POWER SUPPLY Voltage 8.5-15VDC

No-load current 0.5A

Off without DRC 5mm

Off with DRC 4mA

Remote IN voltage 6-15 VDC


Remote output voltage 12V/1.6A/130mA

Signal to Noise Ratio 100dB at 1kHz 100mV RMS output

Bandwidth @ -3dB 20-22kHz

Master input 98 dBA 96dBA

Cross input Channel separation at 1 kHz 65 dB Weighted



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker




<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker



<https://www.advertentiax.nl/x-1243008-z>
 nieuw AudioSystem Italy
 10-kanaals DSP versterker

S / N @ A ratio

Input sensitivity (speaker input) 2-15V RMS

Input sensitivity (Aux In) 0.2-5V RMS

Input sensitivity (telephone) / Input sensitivity (Speaker In) 10kohm

Input Sensitivity (Aux) 22kohm

Maximum OUTPUT level (RMS) at 0.1% THD 4V RMS

ENTRY PHASE High level (speaker) Low level (Pre) CONNECTION From / to personal computer 1 x
USB / B (1.1 / 2.0) 5M CROSSOVER N.5 (one for each output channel)

Filter type Full / High / Low Pass / Band Pass Slope setting 6/12/18/24/30/42/48 dB 68 steps at 20-20 kHz

Independent setting of phase control for each channel 0-180

Software Windows suitable

DRC remote controller

External display / controller for presets and main controls.

MANAGE:

- Subwoofer
- Presets
- Mute
- Volume master

Easy to install

Size: