

# Cisco Meraki MS22 (150 EUR)



Locatie **Noord-Brabant, Eindhoven**  
<https://www.advertentiax.nl/x-1258545-z>

Wegens overcompleet aangeboden Cisco Meraki MS22 switch

24P Gigabit + 4x SFP

Switch is van account losgekoppeld.  
 Niet voorzien van een licentie, deze dient u zelf aan te schaffen.

Werkt 100%, in goed staat. Alleen wat beschadegingen op de bovenkant behuizing

The Cisco Meraki MS22 Cloud-Managed 24 Port Gigabit Access Switch brings the benefits of cloud computing, including management simplicity, reduced complexity, and lower cost, to branch and campus networks.

## Cisco Meraki MS22 Features

24 Port Gigabit Ethernet Switch  
 Voice and Video QoS  
 Low noise, fanless  
 Non-blocking switch fabric  
 Ultra-reliable, includes lifetime warranty  
 Visibility and control over thousands of ports  
 Built-in multi site management  
 Zero touch provisioning

Cisco Meraki MS22 Cloud-Managed 24 Port Gigabit Access Switch is built from the ground up to be easy to manage without compromising any of the power and flexibility traditionally found in enterprise-class switches.

The Cisco Meraki MS22 Cloud-Managed 24 Port Gigabit Access Switch is managed through a convenient, intuitive web interface. All configuration and management is done through the cloud, bringing the benefits of a cloud-managed switch to your network; there is no need for complex configuration files or complex management.

The Meraki MS22 switch is designed for reliable, long-lived operation in wiring closet environments, which may be prone to high temperatures and limited ventilation. By minimizing total component count and only using proven switching silicon, Meraki is able to deliver a mean time between failure (MTBF) ratings of over 45,000 hours on products such as the Meraki MS22.

Note: Please refer to the Meraki Cloud Managed Access Switches Comparison Table for more information.

 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>	 <p><a href="https://www.advertentiax.nl/x-1258545-z">https://www.advertentiax.nl/x-1258545-z</a></p> <p>Cisco Meraki MS22</p>
--	---	---	---	--	---	---	---	---	---

---

## Cisco Meraki MS22 Cloud-Managed 24 Port Gigabit Access Switch Technical Specifications

### Interfaces

24 × 10/100/1000BASE-T Ethernet (RJ45) with auto-MDIX crossover (4 shared with SFP)  
48V DC 802.3af/802.3at Power-over-Ethernet (PoE/PoE+) on the MS22P model, available on all ports (maximum of 30W per port for PoE+)  
4 × SFP Gigabit Ethernet interfaces for uplink  
Auto negotiation and crossover detection

### Ethernet switching capabilities

802.1p Quality of Service prioritization  
802.1Q VLAN tagging and Q-in-Q VLAN stacking with 4096 addressable tags  
802.1D Spanning Tree Protocol (RSTP, STP)  
802.1ab Link Layer Discovery Protocol (LLDP)  
802.3ad link aggregation with up to 8 ports per aggregate  
Broadcast storm control  
IGMP snooping for multicast filtering  
MAC forwarding table entries: 8,000

### Security

Integrated two-factor authentication  
Role-based administration  
Corporate wide password policy enforcement  
IEEE 802.1X port-based security

### Performance

Non-blocking fabric  
48 Gbps non-blocking switching capacity  
2.5 microsecond latency

### Management

Managed via the cloud using the Meraki dashboard  
Integrated with Meraki wireless, routing, and firewall management  
No-touch remote deployment (no staging needed)  
Detailed historical per-port and per-client usage statistics  
DHCP and hostname fingerprinting  
SNMP v2c  
Seamless over-the-web firmware upgrades

### Remote diagnostics

Email and text alerts  
Live remote packet capture  
Aggregated event logs with instant search

### Scalable stacking

Unified configuration and monitoring of all switches  
Virtually stack thousands of switch ports in a single logical stack for unified management, monitoring, and configuration

### Power

Power input: 100-240 VAC, 47-63 Hz  
Power consumption: 22 - 500 W max

### Environment

Operating temperature: 32°F to 104°F (0°C to 40°C)  
Humidity: 5 to 95% non-condensing  
Silent operation for office environments

### Physical dimensions MS22

Weight: 6.1 lbs (2.8 kg)  
17.4"(w) x 11.7" (l) x 1.8" (h) (44.1 x 29.9 x 4.4)