

CISCO Meraki MS120-8LP (250 EUR)



Locatie **Flevoland, Lelystad**
<https://www.advertentiax.nl/x-1259383-z>

Ik heb er nog 3 op voorraad.
 Waarvan 2 zonder doos.
 Per stuk 250 Euro

Interfaces

- 8 x 10/100/1000BASE-T Ethernet (RJ45)
- 2 x 1G SFP ports for uplinks
- Auto-negotiation and crossover detection

Management

- Managed via the Web with the Meraki cloud management platform
- Integrated with Meraki wireless and complete portfolio of IT products and solutions

Zero-touch remote provisioning (no staging needed)

Detailed historical performance and per-client usage statistics

Cloud-managed system, no on-site hardware configuration

SNMP and Syslog support for integration with other network management solutions

Automatic firmware upgrades with scheduling control

| | | | | | | | | | |
|--|---|---|---|--|---|---|---|---|---|
|  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |  https://www.advertentiax.nl/x-1259383-z CISCO Meraki MS120-8LP |
|--|---|---|---|--|---|---|---|---|---|

Remote Diagnostics

Email, SMS, and mobile push notification alerts

Ping, traceroute, cable testing, and link failure detection with alerting

Remote packet capture

Dynamic and interactive network discovery and topology

Combined event and configuration change logs with instant search

Stacking

Virtual Stacking supports thousands of switch ports in a single logical stack for unified management, monitoring, and configuration

Security

Integrated multi-factor authentication for cloud management platform

Role-based access control (RBAC) with granular device and configuration control

Corporate-wide password policy enforcement

IEEE 802.1X RADIUS and MAB, hybrid authentication, and RADIUS server testing

Single-Host/Multi-Domain/Multi-Host/Multi Authentication

Port security: Sticky MAC, MAC whitelisting

DHCP snooping, detection and blocking

IPv4 and IPv6 ACLs

Performance

Switching capacity: 20 Gbps

Forwarding rate: 14.88 mpps

Jumbo frame support (9600 byte Ethernet frame)

Flow control support

Layer 3

DHCP Relay

Power

Power input: 100 - 240 VAC, 47-63 Hz

MS120-8: 6-9 W max, fanless

MS120-8LP: 7-88 W max, fanless

MS120-8FP: 9-162 W max, fanless

48V DC 802.3af/802.3at Power-over-Ethernet (PoE/PoE+) available on all ports (maximum of 30W per port for PoE+) for powered switches

Environment

Operating temperature: 0°C to 45°C

Humidity: 5 to 95% non-condensing

Variable speed fans

Regulatory

CSA-US (US, Canada)

FCC (USA)

IC (Canada)

CE (Europe)

RCM (Australia/New Zealand)

RoHS

MTBF Rating (at 25°C)

MS120-8-HW: 784,221

MS120-8-LP-HW: 502,221

MS120-8-FP-HW: 347,479

Physical Specifications (H x W x D)

MS120-8-HW

1.1" x 8.74" x 5.91" (2.8 x 22.2 x 15cm)

2.36 lb (1.07 kg)

MS120-8LP-HW

1.1" × 8.74" × 5.91" (2.8 × 22.2 × 15cm)

2.36 lb (1.07 kg)

MS120-8FP-HW

1.75" × 8.97" × 8.58" (4.4 × 22.7 × 23cm)

2.36 lb (1.07)