

## cnPilot e400 smart WiFi professioneel acces point 100 (79,99 EUR)



## C000100W400A

Cambium C000100W400A cnPilot E400 (FCC) 802.11ac dual band AP PoE Cat 5 Ethernet

## cnPilot™ E400 Indoor Access Point

Designed for wireless service providers of both enterprise and distributed enterprise networks, cnPilot™E400 offers WLAN that is scalable, secure, and reliable. The enterprise-grade 802.11ac access points support onpremise or cloud management in a solution that rolls out quickly, blends in to the environment and is easy to operate.





Locatie Limburg, Sittard https://www.advertentiex.nl/x-1288143-z



## EXPANDING THE ENTERPRISE.

Designed for wireless service providers of both enterprise and distributed enterprise networks, cnPilotE400 offers WLAN that is scalable, secure, and reliable. The enterprise-grade 802. 11ac access points support on-premise or cloud management in a solution that rolls out quickly, blends in to the environment and is easy to operate.

Cloud Management: backed by Cambiums cnMaestro cloud manager offering end to end visibility of the network and customer devices

Out-of-the box zero touch onboarding

Stateful alarms and dashboard views

Multiple management options available including cloud-based,

SNMP and an enriched set of RESTful interfaces

End-to-end Troubleshooting: Single dashboard view and rich statistics ensure rapid root cause detection

and issue resolution

One-click functionality reveals the health of all network nodes related to the problem area



e400



https://www.advertentiex.nl/x-1288 143-z



https://www.advertentiex.nl/x-1288 143-z smart



https://www.advertentiex.nl/x-1288 143-z professioneel cnPilot acces point



Integration with 3rd party external guest acc selutions is imple deploying to the control of Security: 5 2

Support WPA2 Enterprise and WPA2 PSK Secure confection of er HTTP back to the cloud

smart

for management smart





https://www.advertentiex.nl/x-1288 143-z acces point



smart



**KEY FEATURES:** 

802. 11ac concurrent dual band

2x2 MIMO

16 SSIDs supporting 256 concurrent users

Cloud managed with no on-site controller required

On-board captive portal

Rate limiting per SSID and client

Fast roaming across access points (AP)

Auto channel selection for allocation of wireless