

auto audio (125 EUR)



Locatie Noord-Holland, Amsterdam
<https://www.advertentiax.nl/x-1343078-z>

Te koop.

Zie foto's en specs.

Alles in een koop


De set is doormiddel van xt60 en banaan pluggen binnen 1 minuut in of uitgebouwd. komt uit een f.panda.

i.v.m 24/6 werk kan ik alleen in het weekend reageren!!

Als je zorgt voor voeding (stroom en audio) is testen geen probleem.

Specifications: magnat traveller 320m. treble tweeters of jvc 2 way

Music power RMS / Max.: 90 / 180 Watt
Frequency range: 30 - 24,000 Hz
Impedance: 4 ohms

 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z Specifications: Magnat Anniversary 3000 Laut subwoofer Bass Reflex Enclosure 3 fold reflex tube power system Sensitivity: 91dB Impedance: 4 ohms Frequency range: 30 - 24,000 Hz Music power RMS / Max.: 90 / 180 Watt Frequency range: 30 - 24,000 Hz Impedance: 4 ohms auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio	 https://www.advertentiax.nl/x-1343078-z auto audio
--	---	---	---	--	---	---	---	---	---

Flow-optimized bass reflex openings
300 mm high-performance driver with 2.5" high-performance vibrating coil and polar core ventilation
Chrome-plated low-resonance steel basket
Efficiency-optimized long-stroke bead and coated cellulose membrane
Non-slip upholstery fabric with 3-color design logo stick
Nominal/music capacity: 400 / 1400 Watt / 20 – 200 Hz / 4 Ohm / 93 dB / 95 db
Dimensions (Ø, L): 335 mm, 795 mm / 9.5 kg

Specifications:hifonics 1.0 farad capacitor

1.0 Farad SPL Buffer Capacitor
High-quality shock-resistant aluminum housing
Blue illuminated 4-digit voltage display
blue glowing status tube
large screw connections

Specifications: AMPLIFIER FEATURES

JA948ATX - Amp with Gold Plated Terminals

Tri-Boost MOSFET Technology With 30% Larger Field Effect Magnitude
Externally Variable Amplified Level Controls To Enhance Musical Equalisation & Effect
Active Linkwitz-Riley Design, 18dB/oct, 24dB/oct Cont. Variable Crossovers
Low Noise-Low Distortion Amplification Via BOSCHMANN High Accuracy Common Mode Rejection (HACMR) Technology
Discretely Engineered Advanced Class Amplifier Topology With Low Loss Rate & Improved Transient Response
Fully Automated Insertion Process On High-Value Components That Ensures The Highest Grade Of Amplified Sound Quality
Self-Activating On-Board Schmidt-Trigger Design Protection System For Total Amplifier Safety
Stereo/Mono Connection With Stabilized Minimum Load Operation While Producing a True Bridged Field Effect

AMPLIFIER SPECIFICATIONS

:: Max Output: 1200 Watts
:: 4 Ohms Max Power Output @ 0.035% T.H.D.: 300W x 4ch
:: 4 Ohms Bridged Power Output @ 0.035% T.H.D.: 600W x 2ch
:: 2 Ohms RMS Output @ 0.07% T.H.D.: 150W x 4ch
:: 4 Ohms RMS Output @ 0.035% T.H.D.: 75W x 4ch
:: Low Pass Filter: (Variable) 40Hz-150Hz
:: High Pass Filter: (Variable) 80Hz-1.2kHz

- :: Frequency Response: +1/-1dB : @ 5Hz-50kHz
- :: Signal to Noise Ratio: >100dB
- :: Stereo Separation: >90dB (Stable into 2 Ohms operation)
- :: Damping Factor: 200
- :: Equalizer Controls - Bass Boost: 0/6/12dB
- :: Input Sensitivity: 200mV ~ 6V
- :: Input Impedance: 22K Ohms
- :: Operation Voltage (Negative Ground): DC12V
- :: Speaker Impedance @ Stereo Driven: 4 Ohms
- :: Fuse Rating: 30A x 1
- :: Dimensions (WxHxD): 263mm x 53mm x