

3Com 3crbsg28hpwr93 Baseline Plus Switch 2928 hpwr 24xtpPoE (389 EUR)



Locatie **Zuid-Holland, Wateringen**
<https://www.advertentienx.nl/x-135545-z>

3Com 3CRBSG28HPWR93 Baseline Plus Switch 2928 HPWR (24x TP+PoE, 4xSFP)



2 MARKTPLAATS.nl

Gebuiikte, maar in absolute nieuwstaat verkerende 3COM switch met 24x 10/100Mb en 4x SFP-aansluitingen (waarvan twee gedeeld). Volledig managable. Biedt op alle RJ45/TP aansluitingen ondersteuning voor Power Over Ethernet (PoE). Wordt bulk geleverd inclusief netsnoer.

Affordable, Managed Gigabit PoE Switching with Flexible Uplinks

The "smart" voice-ready 3Com Baseline Plus Switch 2928 HPWR is a web-managed Gigabit Power over Ethernet (PoE) switch with extensive layer 2 functionality and layer 3 static routes. It offers enterprise-class features, customized and priced for small- and mid-sized organizations.

With an easy-to-use switch interface and advanced features (VLANs, IEEE 802.1X authentication and QoS), this switch is the most cost-effective way to provide a converged network.

Power over Ethernet

The Baseline Plus Switch 2928 HPWR provides inline power to attached devices- access points, Voice

over IP (VoIP) phones, IP security cameras, etc - via industry-standard IEEE 802.3af Power over Ethernet (PoE) over a single twisted-pair cable, eliminating the need for separate power cabling.

Managed Gigabit Switching with Advanced Features
 The Baseline Plus Switch 2928 HPWR has up to four 10/100/1000 Mbps (1 Gbps) SFP ports (fiber) to connect to high-performance computers, servers, or core network backbones.

This "smart" switch has the features that help build a voice-ready network, with support for auto-voice VLAN, L2/L3, SNMP-based management, IGMP snooping and IEEE 802.1X and advanced Access Control Lists (ACLs) for strengthening security.

The switch provides non-blocking performance, a 28 ports perform at wire speed which helps to eliminate



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>



3Com 3crbsg28hpwr93
 Baseline Plus Switch 2928
 hpwr 24xtpPoE
<https://www.advertentienx.nl/x-1355>

network traffic bottlenecks. LACP link aggregation (IEEE 802.3ad) allows ports to be automatically grouped together to form an ultra-high-bandwidth connection that greatly expands bandwidth capacity to the network backbone.

The Baseline Plus Switch 2928 HPWR also supports Spanning Tree, Rapid Spanning Tree and Multiple Spanning Tree, traffic prioritization, priority queuing and VLANs. These switching features ensure optimal use of available bandwidth as traffic flow is directed according to the needs of the business.

No Switch Setup Required

This Baseline Plus switch is operational straight out-of-the-box; as long as default settings are acceptable, there is no need to configure the switch. If desired, the switch can be configured using a web browser or SNMP management software.

Enhanced Intuitive Management Options

For networks that require more control, the switch web management interface provides an intuitive, menu driven process for even novice users to quickly and confidently configure the switch during initial setup and manage it during normal operation. Graphical switch and port views provide a clear understanding of switch status and configuration.

In addition, the web interface features individual port-traffic monitoring (port mirroring) and MAC address port mapping tables. A cable diagnostic tool lets users troubleshoot basic connectivity problems via the web management interface further simplifying network installation.

With single IP management, up to 32 devices of the same family (3CRBSGxxx models) can be managed from one IP address via the IRF Lite functionalit.

This Baseline Plus Switch is also supported by IMC (Intelligent Managent Center), 3Com Network Supervisor (3NS) and 3Com Network Director (3ND) management software.

IMC can be used to map the network topology, indicating what devices are connected, and on what ports. Switch management and software upgrades can be easily done. Other SNMP-based management tools may also be used.

The Switch family also supports a compact Command Line Interface (CLI) that is accessed via the front panel console port. Using the CLI, initial switch setup options can be quickly configured.

De volgende extra's zijn beschikbaar:

-3Com SFP 1000BASE-SX 850nm transceiver (3CSFP91) #1 van € 49,95 voor € 44,95

-3Com SFP 1000BASE-SX 850nm transceiver (3CSFP91) #2 van € 49,95 voor € 44,95

U kunt afhalen in Wateringen, of wij sturen de artikelen naar u op. U kunt dan betalen via creditcard, PayPal, rembours, iDEAL of vooruitbetaling!
Uiteraard leveren wij met BTW-factuur, de genoemde prijzen zijn incl. BTW.

That's IT!
'S-GRAVENZANDSEWEG 12
2291 PE WATERINGEN
T 0174-219060

Kijk ook eens naar mijn andere!
Tel: 0174-219060