

Vivotek AW-GET-080A-120 8xGE PoE Switch (35 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiax.nl/x-1413486-z>

Zo goed als nieuw. 8-poorts Switch van Vivotek.



IP Camera Compatibility:

Video Resolution Megapixel/D1/VGA
 Video Compression MJPEG/MPEG-4/H.264/H.265
 Compatible Camera List VIVOTEK Network Cameras

Ethernet:

Gigabit Ethernet (RJ45) 8 Standards
 IEEE 802.3 10-BASE-T (Ethernet) Supported
 IEEE 802.3u 100-BASE-TX (Fast Ethernet) Supported
 IEEE 802.3ab 1000-BASE-T (Gigabit Ethernet) Supported
 IEEE 802.3x Flow Control (Full-Duplex Flow Control) Supported
 IEEE 802.3af Power over Ethernet Supported
 IEEE 802.3at Power over Ethernet Plus Supported
 IEEE 802.3az Energy-Efficient Ethernet Supported

Ethernet Performance:

 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z	 Vivotek AW-GET-080A-120 8xGE PoE Switch https://www.advertentiax.nl/x-1413486-z
---	--	--	--	---	--	--	--	--	--

1000Mbps 1,488,000 pps

Transmission Media:

10Base T Cat. 3, 4, 5 UTP/STP

100Base TX Cat. 5, 5e UTP/STP

1000Base T Cat. 5e, 6, 7 UTP/STP

PoE Function:

Number of PoE Out Ports 8

PoE Power Output Per Port 56VDC, Max. 30W

Total PoE Power Budget 115 W

802.3at/af Standard Compatible Yes

Over Current Protection Supported

Circuit Shorting Protection Supported

Power Pin Assignment 1/2(+), 3/6(-)

PoE PD Auto Detection Yes

General:

LED Indicators Power, Act x8, 100Mx8, 1000Mx8, PoE ports x8

Power Input 100~240V AC / 50~60Hz

Power Consumption 120 W

Operating Temperature 0°C ~ 50°C (32°F ~ 122°F)

Storage Temperature -20°C ~ 70°C (-4°F ~ 158°F)

Operating Humidity 10~90% (Non-condensing)

Dimensions 280 (L) x 182 (W) x 44 (H) mm

Weight 1.6 kg

Safety Certifications CE, C-Tick, FCC, LVD, VCCI

Kijk ook eens bij mijn andere.