

GAS GAS EC 300 STD Elektrische start (8 EUR)



Locatie Zuid-Holland, Giessenburg
<https://www.advertentiax.nl/x-147217-z>

GasGas EC 300 Electrictrische start uit voorraad leverbaar!

MET GRATIS HGS UITLAATSYSTEEM

Prijs is incl. BTW en BPM

Specificaties:


Engine
 2-stroke Single-cylinder, liquid-cooled

Displacement
 299,3 cc

Bore x stroke
 72,0 x 72,0 mm



2 MARKTPLAATS

 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z	 GAS GAS EC 300 STD Elektrische start https://www.advertentiax.nl/x-147217-z
--	---	---	---	--	---	---	---	---	---

Clutch
Multidisc in oil bath

Carburettor
Keihin PKWS 38 mm

Intake system
Reed valve

Exhaust muffler
Reverse

Bodywork
Unbreakable plastic

Handlebar
Aluminium

Frame
Perimeter frame in chrome-molybdenum

Subframe
Tubular aluminum alloy

Swingarm
Aluminium, progressive system with tie rods

Front fork
Marzocchi Shiver invertida Ø45 mm

Suspensión travel
298 mm

Adjustability
Spring preload, rebound and compression

Shock absorber
Sachs mono shock

Adjustability
Spring preload, rebound and compression

Suspension travel
298 mm

Rim type
Morad Aluminium spoke rim

Rim - tyre
Front: 1.6 x 21 - Metzeler Six Days Extreme 90/90 - 21

Rim - tyre
Rear: 2.15 x 18 - Metzeler Six Days Extreme 140/80 - 18

Front brake
260 mm Galfer wave disc, 2-piston Nissin caliper

Rear brake
220 mm Galfer wave disc, 1-piston Nissin caliper

Fuel

9,5 l (2T oil mixed with gasoline 1:50)

Dry weight

107 kg / 112 kg

Dimensions

Length x width x height: 2.200 x 830 x 1.260 mm

Wheelbase

1.480 mm

Seatheight

950