

# 3Com 3CRS42G-24P-91 (449,95 EUR)



Locatie

<https://www.advertentieX.nl/x-1554040-z>

Zuid-Holland, Wateringen

Deze switch is refurbished en verkeert in perfecte technische staat.

HP 4210G Switch Series are entry-level Gigabit Ethernet LAN switches with enterprise-class quality of service (QoS), security, and management features, delivering high value for network administrators looking for an economical edge device. Available Power over Ethernet (PoE) models are ideal for voice over IP and wireless networking installations, while non-PoE models are also available for simple port expansion. Dual-personality ports allow flexibility, including the ability to add 10 Gigabit Ethernet capability. Setting them apart from lower-end devices, the series switches support an industry-standard command-line interface, Web-based administration, and SNMP management. In addition, they support Intelligent Resilient Framework (IRF) stacking of up to four units. Features and benefits

Layer 4 prioritization: enables prioritization based on TCP/UDP port numbers

Traffic prioritization (IEEE 802.1p): allows real-time traffic classification into eight priority levels mapped to eight queues

Class of Service (CoS): sets the IEEE 802.1p priority tag based on IP address, IP Type of Service (ToS), Layer 3 protocol, TCP/UDP port number, source port, and DiffServRate limiting: sets per-port ingress enforced maximums and per-port, per-queue guaranteed minimums

Bandwidth shaping: Rate limiting: provides per-port, ingress-based enforced bandwidth maximums

Guaranteed minimums: provides per-port, per-queue egress-based guaranteed bandwidth minimums

Broadcast control: allows limitation of broadcast traffic rate to cut down on unwanted broadcast traffic on the network

Management: Remote configuration and management: is available through a secure Web browser or a command-line interface (CLI)

Manager and operator privilege levels: enable read-only (operator) and read-write (manager) access on CLI and Web browser management interfaces

Management VLAN: segments traffic to and from management interfaces, including a Web-based interface, a command-line interface (CLI), and support for centralized RADIUS accounting server, static SSID, broadcast, detailed service usage, and configuration for each port

ActivityMonitor: configuration files are stored in a central image file, providing independent summary and detailed log files while updating the configuration

Secure Web GUI: provides a secure, easy-to-use graphical interface for configuring the module via HTTPS

Command-line interface (CLI): provides a secure, easy-to-use command-line interface for configuring the module via SSH or a switch console; provides direct real-time session visibility

SNMPv1, v2c, and v3: facilitates centralized discovery, monitoring, and secure management of networking devices

Port mirroring: enables traffic on a port to be simultaneously sent to a network analyzer for monitoring

ConnectivityOptions: 10 Gigabit Ethernet ports: allow the addition of 10 Gigabit Ethernet connections for uplinks or high-bandwidth server connections; flexibly supports XFP, SFP+, or CX4 local

 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>	 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>	 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>	 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>
3Com 3CRS42G-24P-91	3Com 3CRS42G-24P-91	3Com 3CRS42G-24P-91	3Com 3CRS42G-24P-91
 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>	 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>	 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>	 <a href="https://www.advertentieX.nl/x-1554040-z">https://www.advertentieX.nl/x-1554040-z</a>
3Com 3CRS42G-24P-91	3Com 3CRS42G-24P-91	3Com 3CRS42G-24P-91	3Com 3CRS42G-24P-91

---

connectionsAuto-MDIX: automatically adjusts for straight-through or crossover cables on all 10/100 and 10/100/1000 portsDual-personality functionality: includes four 10/100/1000 ports or SFP slots for optional fiber connectivity such as GigabitSX, -LX, -LH, or 100-FXIEEE 802.3af Power over Ethernet (PoE): provides up to 15.4 W per port to IEEE 802.3af-compliant PoE-powered devices such as IP phones, wireless access points, and security cameras

Klik op de link om direct te bestellen! Gratis verzending vanaf €100,-Website [www.nowthatsit](http://www.nowthatsit)