

Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe) (200 EUR)



Locatie Overijssel, Almelo
<https://www.advertentiax.nl/x-1575188-z>

Buitenkant heeft lichte krasjes, heeft los gelegen in serverkast, helaas geen beugels.
 Verder in topconditie en ik zoek één nieuw huis/ eigenaar die mij weer voor 100% wil in zetten, ben een echt werkpaard!

Technical Specifications
 US-8-150W
 Dimensions 204 x 43 x 235 mm (8.03 x 1.69 x 9.25")
 Weight
 Without Mount Brackets
 1.65 kg (3.64 lb)
 With Mount Brackets
 1.73 kg (3.81 lb)
 Networking Interfaces (8) GbE RJ45 Ports
 (2) 1G SFP Ports
 Management Interfaces Ethernet In-Band
 Power Method 100-240V AC/50-60 Hz, Universal Input
 Power Supply AC/DC, Internal, 150W DC
 Max. Power Consumption
 Including PoE Output
 Excluding PoE Output

 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)	 https://www.advertentiax.nl/x-1575188-z Ubiquiti Unfi Switch 8 Ports 150 watt (netto 110 watt Poe)
---	--	--	--	---	--	--	--	--	--

Link/Speed/Activity

PoE Output (RJ45 Ports) PoE/PoE+ 2-Pair (+1, 2; -3, 6);

Passive 24V/0.7A 2-Pair (+4, 5; -7, 8)

ESD/EMP Protection $\pm 24\text{kV}$ Air, $\pm 24\text{kV}$ Contact

Shock and Vibration ETSI300-019-1.4 Standard

Operating Temperature -5 to 45° C (23 to 113° F)

Operating Humidity 5 to 95% Noncondensing

Certifications CE, FCC,