

HPE Proliant ML150 Gen9 E5-2609V3 32Gb 4Lff Server (175 EUR)



Locatie **Groningen, Tolbert**
<https://www.advertentieX.nl/x-1598871-z>

Te koop

Zo goed als nieuwe HPE Proliant ML150 Gen9 Server. Gaat weg omdat hij niet meer gebruikt word.De server is compleet geformatteerd en dus direct gereed voor gebruik. Ook is de server nog verder uit te breiden door middel van een extra CPU, Werkgeheugen en Hdd's

Ook is de server te gebruiken als Workstation.

Er zitten hier 4x HPE 1TB 6G SAS 7.2K 3.5-inch in en een extra storage controller in P440 Smart Array

General Information :

Manufacturer : Hewlett Packard Enterprise

Manufacturer Part Number : 776275-001 ?????

Product Name: Proliant ML150 Gen9 - 5u Tower Server (Entry Model)

Processor & Chipset :

Processor Type : Intel Xeon E5-2609v3/ 1.9ghz

Quickpath Interconnect : 6.4 Gt/s

Number Of Cores : 6-core

64-bit Computing : Yes

Compatible Processor Socket : Fc1ga2011-3

Cache Memory :

Cache Memory Type: Smart Cache

Cache Memory Size : 15MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB

Cache Processor : 15 MB




HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server




HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server



HPE Proliant ML150 Gen9
E5-2609V3 32Gb 4Lff Server

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

<https://www.advertentieX.nl/x-1598871-z>

Technology : Ddr4 Sdram - Advanced Ecc
Effective Memory Speed : 1600 Mhz
Rated Memory Speed : 2133 Mhz
Memory Specification Compliance : Pc4-17000
Form Factor : Dimm 288-pin
Slots : 16 (total) / 15 (empty)
Features : Registered, Online Spare Memory, Quad Channel Memory Architecture, Hp Smartmemory
Configuration Features : 4 X 8 Gb
Ram Supported : Pc4-17000 - 256 Gb Load-reduced Pc4-17000 - 256 Gb Registered

Storage:

Hard Drive : 4x HPE 1TB 6G SAS 7.2K 3.5-inch
4TB in totaal

Optical Drive : DVD RW

Storage Controllers:

1

HP Smart Array P440/2GB FBWC 12GB Single Port PCI-E 3.0 X8 SAS Controller
Manufacturer: HP Category: Proliant Controller Sub-Category: Smart Array Generation: P440/2GB Part
Number: 726823-001 Products ID: 725474 Product Type: Storage Controller (RAID) Host Bus: PCI
Express 3.0 x8 Controller Interface Type: SATA 6Gb/s SAS 12Gb/s Data Transfer Rate: 1.2GB/s Buffer
Size: 2GB RAID Level: 0 1 1 ADM 10 10 ADM 5 50 6 60 Supported Devices: Disk Array (RAID), Hard
Drive Channel Quantity: 8 Form Factor: Low-Profile Plug-in Card

2

Storage Controller Name : Smart Array B140i
Buffer Size : None
Disk Drive : Up To 6gb/s Sata (serial Ata)
Connectors : 10 Internal Sata Connectors
Server Interface : X4 Pcie 2.0
Sata Speed : 6gb/s Sata Links
Logical Drives Supported : Up To 8 Logical Volumes (6 Physical Drives)
Host Memory Addressing : 64-bit, Supporting Greater Than 4gb Server Memory Space
Raid Support : Raid 0, Raid 1, Raid 5, Raid 10, Raid 50

Network & Communication :

Type : Integrated
Interface (bus) Type : Pci Express X2
Ethernet Ports : 2 X Gigabit Ethernet

Ethernet Controller : Hp 331i
Data Link Protocol : Ethernet, Fast Ethernet, Gigabit Ethernet
Remote Management Protocol : Ipmi 2.0, Smash Clp
Remote Management Controller : Integrated Lights-out 4
Features : Wake On Lan (wol), Pxe Support
Compliant Standards : Ieee 802.3, Ieee 802.3u, Ieee 802.3ab

Power Description :
Device Type : Flex Slot Platinum Plus Power Supply.
Installed Qty :
Nominal Voltage : Ac 120/230 V (50/60 Hz)
Power Provided : 2x 550 Watt

Expansion/ Connectivity :
Expansion Bays Total (free) :
1 (total) / 1 (free) X External 5.25
4 (total) / 4 (free) X Internal 3.5 Lff

Expansion Slots Total (free) :
16 (total) / 15 (free) X Dimm 288-pin
2 (total) / 1 (free) X Cpu
4 (total) / 3 (free) X Pcie 3.0 X8 - Half-length, Full-height
2 (total) / 2 (free) X Pcie 3.0 X16 - Full-length, Full-height
1 (total) / 1 (free) X Microsd Card (internal)

Interfaces & Ports :
1 X Vga
2 X Lan (gigabit Ethernet)
1 X Hp Ilo
5 X Usb 3.0 (2 Front, 2 Rear, 1 Internal)
3 X Usb 2.0 (2 Rear, 1 Internal)

Miscellaneous :
Features :
Administrator Password
Power-on Password
Serial Port I/o Control
Setup Password
Uefi Bios

Dimensions & Weight :

Depth : 24.4 Inch

Width : 7.9 Inch

Height : 17 Inch

Weight : 37.3