

Ubiquiti UniFi Switch Pro 24 PoE (400W) (715 EUR)



Locatie **Limburg, Heerlen**
<https://www.advertentiex.nl/x-1743007-z>

Te koop aangeboden:

Ubiquiti UniFi Switch Pro 24 PoE (400W) nieuw in gesealde doos.
Wordt geleverd met garantie en btw factuur.



UnifyMechanical

Dimensions

442.4 x 285.4 x 43.7 mm (17.4 x 11.2 x 1.7")

Weight

Without mounting brackets: 4.3 kg (9.5 lb)

With mounting brackets: 4.4 kg (9.7 lb)

Enclosure material

SGCC steel

Hardware

Management interface

Ethernet In-Band

Networking interface

(24) GbE RJ45 ports

(2) 1/10G SFP+ ports

PoE interface



Ubiquiti UniFi Switch Pro 24 PoE (400W)




<https://www.advertentix.nl/x-1743007-z>



<https://www.advertentia.nl/x-1743007-z>




<https://www.advertentia.nl/x-1743>
007-Z




Ubiquiti UniFi Switch Pro 24 PoE (400W)




<https://www.advententex.nl/x-1743007-z>




<https://www.advertentex.nl/x-1743007-z>



<https://www.advertentia.nl/x-1743007-z>



<https://www.advertentie.nl/x-1743>
007-z



<https://www.advertentix.nl/x-1743007-z>

Ubiquiti UniFi Switch Pro 24 PoE (400W)

AC/DC, internal, 450W
Supported voltage range
100—240V AC
Max. power consumption
50W (Excluding PoE output)
Total available PoE
400W
Max. PoE wattage per port by PSE
PoE+: 32W
PoE++: 64W
Voltage range PoE mode
PoE: 44—57V
PoE+: 50—57V
ESD/EMP protection
Air: $\pm 16\text{kV}$, contact: $\pm 12\text{kV}$
LCM display
(1) 1.3" touchscreen
Button
Factory reset
Shock and vibration
ETSI300-019-1.4 Standard
Operating temperature
-5 to 40° C (23 to 104° F)
Operating humidity
10 to 90% noncondensing
Certifications
CE, FCC, IC
LEDs
System
Status
Ethernet
PoE
Speed/link/activity
SFP+
Link/activity
RPS