

IBM PCserver 704 (99 EUR)





Locatie Zuid-Holland, Wassenaar
<https://www.advertentiax.nl/x-176890-z>

Beste,
 Hier nog een collectors item! Het betreft een IBM PCserver 704
 Er zit 256MB SIMM geheugen in en 2 PPro CPU's 512KB cache
 HDD's en/of controllers NIET meegeleverd!
 Er mist een soort bezel rond de 5,25 drivebay!

De volgende specs zijn door IBM opgeleverd:

At a glance
 Processor type Pentium Pro 200MHz
 Number of processors standard / maximum 1/4
 Level 2 cache 512KB per processor / 512KB per processor
 Memory standard/maximum 256MB / 2000MB
 Disk Subsystem 2 x Wide Ultra SCSI and PC ServeRAID SCSI Adapter and Wide Ultra SCSI RAID (IBM PC ServeRAID SCSI Adapter) and 2 x Wide Ultra SCSI (PCI 32-bit on planar), 0MB installed
 Hard disk type Open bay
 Maximum storage capacity 109.2GB
 Slots and bays (total/available) 10(9) x 17(15)
 CD-ROM 8X
 Network interface

 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z	 IBM PCserver 704 https://www.advertentiax.nl/x-176890-z
---	--	--	--	---	--	--	--	--	--

Countries of origin United States
Ship group System unit
System configuration diskettes
Video support diskette
SCSI PCI support package
IDE CD-ROM device driver diskette
ServeRAID support package
Hardware accessory kit
Four drop narrow SCSI cable
System unit power cords (3)
keyboard with attached cable
PC Server 704 system library
PC Server 704 setup sheet
PC Server 704 diagnostic diskette
IBM NetFinity CD and documentation
ServerGuide
IBM NetFinity 5.0
Lotus Domino R4.5 (single processor edition)

Warranty

Limited Warranty period and type Three year On-site

Architecture

Form factor Tower (10x17)
Orientations allowed Vertical
Bus type/architecture PCI/EISA
Slots x bays total (free) 10(9) x 17(15)
Expansion bus type PCI/EISA

Processor

Processor (CPU) Pentium Pro
Processor internal clock speed 200MHz
Planar clock speed 66MHz
Number of processors standard/maximum 1/4
Processor manufacturer Intel
SMP capable Yes
Math co-processor Built in
L1 internal CPU cache 16KB
L2 external CPU cache standard/maximum 512KB per processor/512KB per processor
L2 external CPU cache type Write-back

L3 cache 0 bytes
Upgradeable processor Yes
Processor upgrade options SMP via up to 4 Pentium Pros
Processor upgrade method Add processor in 387-pin ZIF
BIOS type Flash

Memory
Memory (RAM) standard/maximum 256MB / 2000MB
RAM speed 60ns
Optional RAM configuration 72-pin SIMMs (matched sets of 4:8:16 required)
RAM type ECC Controller with parity memory
RAM slots total (available) 16 (12)

Hard disk
Number of installed hard disks 0
Hard disk size 2.14GB
Hard disk controller 2 x Wide Ultra SCSI and PC ServeRAID SCSI Adapter and Wide Ultra SCSI RAID (IBM PC ServeRAID SCSI Adapter) and 2 x Wide Ultra SCSI (PCI 32-bit on planar)
Hard disk type Open bay
Maximum internal hard disk capacity 109.2GB
Hard disk average seek time 9ms
Average latency 4.17ms
RAID levels supported 0, 1, 5
Hot swappable drive bays 12 / 12

CD-ROM
CD-ROM speed 8X
CD-ROM interface type IDE
CD-ROM data transfer rate 1200 KBps
CD-ROM average access time 160 ms

Graphics Subsystem
Graphics chipset
Graphics type SVGA
Graphics data width 16 bit
Video RAM standard/maximum 0.512MB / 0.512MB
Video RAM type DRAM
Maximum resolution (with standard video RAM) 1024 x 768 x 16 colors
Maximum resolution (with maximum video RAM) 1024 x 768 x 16 colors
Maximum colors (with standard video RAM) 256

Maximum colors (with maximum video RAM) 256

Graphics bus interface PCI

Communications

Fax / modem Optional

Networking

Networking interface Ethernet

Network speed 10Mbps, 100Mbps

Network features RJ-45 connector (for 10Base-T/UTP 3), RJ-45 connector (for 100Base-TX/UTP 5)

Standard features

Pointing device type Enhanced mouse

Standard diskette size 3.5" 1.44MB

Keyboard type Basic 101 key (rubber dome)

Product approvals / certifications CE MARK (EN 55022 Class B) (EN 50082-1) (EN 61000-3-2);

CISPR-22 Class B; CISPR-22 Class B (New Zealand); CSA No. 950; FCC Class B - Part 15: I20 Ready;

IEC-950/EN 60950; IEC-IEC950; NOM (Mexico); TUV-GS (EN 60950/IEC-950); UL-1950; VCCI Class 1;

ZH 1/618/10.80

Power Management

Power supply 3 x 420 Watts

Power supply type 110 or 220 volt hot swap

Power supply additional

Heat emissions 44 Watts

Sound emissions 55dB

Cooling system 3 fans in addition to fans in each power supply

UPS Optional

Expansion Options

Slots total (free) and type 4(4) EISA fullsize, 6(5) PCI fullsize

3.5" bays

- accessible (free) and height 13(12) SL

- not accessible (free) and height 0(0)

5.25" bays

- accessible (free) and height 4(3) HH

- not accessible (free) and height 0(0)

Plug and play support Yes

Parallel ports (type) 1 (ECP/EPP/IEEE 1284)

Serial ports (type) 2

Expansion ports Display, Keyboard, Mouse, SCSI

Weight and Dimensions

Weight 105 lbs

Height 27.5 inches

Width 18 inches

Depth 25 inches

Security

Security features Diskette disable

Keyboard/mouse secure mode

Keyboard lockout timer

Mechanical locks

Power on password

Supervisor password

VPD support Yes

Voorwaarden voor aankoop zijn:

Dat een volwassene de aankoop doet dus 18 jaar of ouder!

U dient verstand van deze artikelen te hebben want het is 2de hands en er is dus geen garantie!

Er worden GEEN andere artikelen onder deze advertentie meegeleverd als ik dit niet specifiek heb vermeld!

Bod of prijsopvraag via mail zal niet in behandeling worden genomen!

M.v.g.