## Advertenticant

## FS s3410-10tf-p Managed switch (nieuw) (200 EUR)





Locatie **Zuid-Holland, Bergschenhoek** https://www.advertentiex.nl/x-1826955-z

FS s3410-10tf-p Managed switch (nieuw) Fanless

Ongebruikt, nooit aangesloten geweest. Gekocht voor een project maar bleek uiteindelijk niet nodig.

10-Port Gigabit Ethernet L2+ PoE+ Switch, 8x PoE+ Ports @125W, with 2x 1Gb SFP Uplinks, Broadcom Chip, Fanless

S3410-10TF-P 10-port managed PoE+ switch is equipped with 10x 10/100/1000BASE-T ports and 2x 1Gb SFP uplinks. 8x RJ45 ports support both IEEE 802.3af PoE and IEEE 802.3at PoE+ (up to 30W per port) for powering attached IP phones, wireless access points, or other standards-compliant PoE and PoE+ end network devices. Fanless design ensures noise-free switch operation, reduced cost and power consumption. The stability of the switch is guaranteed by the use of Broadcom Chips. Secure and simple access for users and IoT with FS Airware Cloud. This energy-efficient access switch delivers a compact and cost-effective solution for small open office deployments and commercial applications.

Specifications

Ports

	FS s3410-10tf-p M switch  FS s3410-10tf-p M switch	lanaged (nieuw) lanaged (nieuw) lanaged (nieuw) lanaged (nieuw) lx-1826 l/x-1826 l/x-1826 l/x-1826
	switch  https://www.advertentiex.nl 955-z  FS s3410-10tf-p M switch  https://www.advertentiex.nl 955-z	
A State of the least of the lea	switch Ching N55-2 Swww.Bdvertstiex.nl	lanaged (nieuw)
	FS s3410-10tf-p M switch  https://www.advertentiex.nl	lanaged (nieuw)
	FS s3410-10tf-p M switch https://www.advertentiex.nl 955-z	lanaged (nieuw)
	FS s3410-10tf-p M switch https://www.advertentiex.nl 955-z	lanaged (nieuw) l/x-1826
	FS s3410-10tf-p M switch https://www.advertentiex.nl 955-z	lanaged (nieuw) I/x-1826

**Switching Capacity** 40 Gbps ARP Table 1000 Forwarding Rate 30 Mpps Number of VLANs 4K Max. Power Consumption 20W (165W with PoE) MAC Address 16K Power Budget 125W Jumbo Frame 9,216 Flash Memory 256MB Total number of IPv4 routes

Not support

Packet Buffer

1.5MB

Management

SNMPv1/v2/v3, RMON, Syslog, sFLOW, CLI, WEB

Power Supply

1 Built-in

Dimensions (HxWxD)

1.73"x13.39"x10.24" (44x340x260mm)

Fan Number