

Cisco 2 port phone Adapter SPA112 (35 EUR)



Locatie **Gelderland, Harderwijk**
<https://www.advertentiex.nl/x-1865092-z>

Cisco 2 port phone Adapter SPA112
Inclusief voeding

2 stuks beschikbaar

Stemcodecs

G.711Mu, G.711a, G.726, G.729A, G.729ab

Veiligheid


Regulatory standards: UL 60950 Second Edition, CAN/CSA-C22.2 No. 60950 Second Edition, IEC 60950-1:2005 (Second Edition) + A1:2009 + A2:2013 and/or AS/NZS 60950.1:2015

Certificering: CE Markings per directives 2014/30/EU and 2014/35/EU

Network



Cisco 2 port phone Adapter
SPA112




Cisco 2 port phone Adapter
SPA112

<https://www.adventenitex.nl/x-1865>
092-z



Cisco 2 port phone Adapter
SPA112

<https://www.advertentiax.nl/x-1865>
092-z



Cisco 2 port phone Adapter
SPA112

<https://www.advertentix.nl/x-1865>
092-z



Corroep-man
Nummerher
Conferentie



<https://www.adventix.nl/x-1865-092-0>
 Cisco 2 port phone Adapter SPA112
 mogelijk




Cisco 2 port phone Adapter
SPA112

<https://www.advertentix.nl/x-1865>
092-z




Cisco 2 port phone Adapter
SPA112
<https://www.advertentiax.nl/x-1865>
092-z



Cisco 2 port phone Adapter
SPA112

<https://www.advententix.nl/x-1865>
092-z



Cisco 2 port phone Adapter
SPA112

<https://www.advertentix.nl/x-1865>
092-z

Wachtstand

Protocollen

VoIP protocollen: SIP

Ondersteunde netwerkprotocollen: TCP, UDP, RTP, HTTP, ARP, RTCP, ICMP, LLDP

Beheerprotocollen: SNMPv3

Ondersteunde beveiligingsalgoritmen: AES, HTTPS, SSH

Beveiliging

DMZ support

Poorten & interfaces

Aantal Ethernet LAN (RJ-45)-poorten: 1

Modem (RJ-11) poort: 2

Logistieke gegevens

Code geharmoniseerd systeem (HS): 85177900

Eisen aan de omgeving

Bedrijfstemperatuur (T-T): 0 - 40 °C

Temperatuur bij opslag: -10 - 60 °C

Relatieve vochtigheid in bedrijf (V-V): 10 - 90 procent

Luchtvochtigheid bij opslag: 10 - 95 procent

Gewicht en omvang

Afmetingen (B x D x H): 100 x 100 x 28 mm

Gewicht: 132,1