AdvertentieX.nl

Unifi switch 24 PoE 2nd gen (250 EUR)

Locatie **Overijssel, Almelo**
https://www.advertentiex.nl/x-1921185-z

De USW-24-POE wordt gemanaged in de UniFi Network Controller en via de UniFi smartphone app. Deze omgeving biedt geavanceerde Layer 2 switch mogelijkheden, zoals operation mode (switching, mirroring of aggregate) per poort. De UniFi Network Controller en mobiele app zorgen voor eenvoudige monitoring en configuratiemogelijkheden in een gebruikersvriendelijke en overzichtelijke omgeving.

Let op: Alleen poorten 1-16 ondersteunen PoE/PoE+

Specificaties USW-24-POE

Afmetingen: 442.4 x 200 x 43.7 mm (17.42 x 7.87 x 1.72")
Gewicht: 3.00 kg (6.61 lb)
Met beugels: 3.09 kg (6.81 lb)
Netwerk Interface:
- Netwerk: (24) 10/100/1000 RJ45 Poorten, (2) 1G SFP Ethernet Poorten
- Management: Ethernet In-Band
Totale Non-Blocking Throughput: 26 Gbps
Switching Capaciteit: 52 Gbps
Doorvoersnelheid: 38.69 Mpps
Power Methode: 100-240VAC, 50/60 Hz, Universele Input
Voeding: AC/DC, Intern, 120W
Voltage Range 100 to 240VAC: 100 to 240VAC
Max. Power Consumption (exclusief PoE): 20.4W / 25W
LEDs:
- System Status
- RJ45 Poorten: Snelheid/Link/Activiteit
- SFP Data Poorten: Link/Activiteit
ESD/EMP Bescherming: Air: +/- 16 kV, Contact: +/- 12 kV
Shock and vibratie: ETSI300-019-1.4 Standaard
Werktemperatuur: -5 to 40 C (23 to 104 F)
Max. luchtvochtigheidsgraad: 10 - 90% Noncondensing
Certificeringen: CE, FCC,

Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z
Unifi switch 24 PoE 2nd gen https://www.advertentiex.nl/x-1921185-z