
1 x Mini USB port on front panel
1 x Micro SD card slot on front panel
1 x Line-out, Mic (on the left)
VGA port (DB-15 connector)
HDMI port
Power switch
AT/ATX switch
Reset button
Clear CMOS button
9 ~ 36V DC input jack
SSD
N/A
Audio
AMP 2W + 2W (internal speaker)
Camera
2 M pixels with low light function
RFID Reader
EM 125 KHz or Mifare 13.56 MHz card reader (optional)
MSR Card Reader
MSR card reader (optional)
OSD Function
LCD on/off, brightness up/down, volume up/down, Hot Key
TPM
Reserved by pin-header
Ethernet
Realtek RTL8111E PCIe GbE controller supporting ASF 2.0
Infrared Remote Control
Yes
Ambient Light Sensor
Yes
Expansion
1 x PCIe Mini slot reserved
Wireless
IEEE 802.11b/g/n 2T2R module (WIFI-RT5392-SB-R10) Telec certified
Bluetooth
Bluetooth V2.0+EDR with USB interface (optional)
HDD Drive Bay
2.5" SATA 3Gb/s HDD bay
CD-ROM Drive Bay
1 x Slim Type CD-ROM bay

Touch Screen
5-wire rsistive type with RS-232 interface / projected capacitive type with USB interface
Cooling System
Light fanless (smart fan operates above default temperature setting)
Drive Bay
1 x Slim Type CD-ROM bay
Construction Front Panel
PC + ABS Plastic
Mounting
Panel, Wall, Stand, Arm VESA 100mm x 100mm
LED Function
LED Light Bar
Front Panel Color
Black
Dimension (WxHxD) (mm)
488 x 361 x 65
Operating Temperature (°C) (Ambient with air flow)
-20°C ~ 40°C
Storage Temperature (?)
-20°C ~ 60°C
Humidity
10% to 95% (non-condensing)
Weight
7.3 kg / 10 Kg
IP Level(front panel)
IP 64 compliant front panel
Safety
CE / FCC
Power Adapter
120W power adapter Input:100 V AC ~ 240 V AC, 50 / 60Hz, Output: 19 V DC
Power Requirement
9 ~ 36 VDC
Power Consumption
19V@5.58A (Intel® Core™ i3-2100T CPU with 4GB 1333 Mhz 4GB DDR3 memory)
Touch Controller
PenMount DMC9000 / EETI EXC7200 & EXC5404
Audio Codec
Realtek ALC892 HD Audio codec
Input / Output
1 x Mic (on the left)

1 x VGA port (DB-15 connector)
1 x HDMI port
1 x Power switch
1 x AT/ATX switch
1 x Reset button
1 x Clear CMOS button
1 x 9 ~ 36V DC input jack
1 x Type K connector
System Cooling
Light fanless (smart fan operates above default temperature setting)
Power Supply
120W power adapter , Input:100 V AC ~ 240 V AC, 50 / 60Hz, Output: 19 V DC
Filter criteria
Applications
Digital Signage
Screen Size
19"
Resolution
1440x900
Touch
resistive
Socket
(with Processor)
Processor
Core I
Clock Speed
2.7GHz
RAM Capacity
4 GB
Status
Phased out
Manufacturer
IEI
Customs Tariff Number
84714100
WEEE Number
DE