


Ubiquiti US-48-750 poe switch, extra bonus in advertentie (324,99 EUR)



Locatie **Overijssel, Almelo**
<https://www.advertentiax.nl/x-1974237-z>

Ubiquiti US-48-750 watt
 Bij het bieden van de vraagprijs is verzending met PostNL inclusief.
 De afgebeelde SFP, een voor glasvezel en een voor UTP, zijn inclusief bij het bieden van de vraagprijs!
 Anders €45,= met zijn 2!

Management interface Ethernet In-Band
 (1) RJ45 Serial port Out-of-Band
 Networking interface (48) GbE RJ45 ports
 (2) 1G SFP ports
 (2) 1/10G SFP+ ports
 PoE interface (48) PoE/PoE+ (Pins 1, 2+; 3, 6-)
 24V DC passive PoE (Pins 4, 5+; 7, 8-)
 Total non-blocking throughput 70 Gbps
 Switching capacity 140 Gbps
 Forwarding rate 104.16 Mpps
 Power method Universal input, 100—240V AC, 50/60 Hz
 Power supply AC/DC, internal, 750W
 Supported voltage range 100—240V AC
 Max. power consumption Excluding PoE output: 64W

 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z	 Ubiquiti US-48-750 poe switch, extra bonus in advertentie https://www.advertentiax.nl/x-1974237-z
--	---	---	---	--	---	---	---	---	---

12.1 dBr

18.1 dBr

21.6 dBr

24.7 dBr

- Background noise level: 27.5 dBa.

Shock and vibration ETSI300-019-1.4 Standard

Ambient operating temperature -5 to 40° C (23 to 104° F)

Ambient operating humidity 5 to 95% noncondensing

Certifications CE, FCC,