

Cisco ASA 5510 firewall (50 EUR)



Locatie **Flevoland, Almere**
<https://www.advertentiax.nl/x-2087265-z>

ciscoasa# sh ver


Cisco Adaptive Security Appliance Software Version 9.1(7)32
 Device Manager Version 6.4(5)

Compiled on Tue 04-Sep-18 08:37 by builders
 System image file is "disk0:/asa917-32-k8.bin"
 Config file at boot was "startup-config"

ciscoasa up 9 mins 49 secs

Hardware: ASA5510, 1024 MB RAM, CPU Pentium 4 Celeron 1600 MHz,
 Internal ATA Compact Flash, 256MB
 BIOS Flash M50FW016 @ 0xffff00000, 2048KB

Encryption hardware device : Cisco ASA-55xx on-board accelerator (revision 0x0)
 Boot microcode : CN1000-MC-BOOT-2.00
 SSL/IKE microcode : CNlite-MC-SSLm-PLUS-2.08
 IPSec microcode : CNlite-MC-IPSECm-MAIN-2.09
 Number of accelerators: 1

 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>	 <p>https://www.advertentiax.nl/x-2087265-z</p> <p>Cisco ASA 5510 firewall</p>
--	---	---	---	--	---	---	---	---	---

```

0: et0/0 : address is 30f7.0000.0000, irq 9
1: et0/1 : address is 30f7.0000.0000, irq 9
2: et0/2 : address is 30f7.0000.0000, irq 9
3: et0/3 : address is 30f7.0000.0000, irq 9
4: Ext: Management0/0 : address is 30f7.0000.0000, irq 11
5: Int: Not used : irq 11
6: Int: Not used : irq 11
    
```

Licensed features for this platform:
 Maximum Physical Interfaces : Unlimited perpetual
 Maximum VLANs : 100 perpetual

Inside Hosts : Unlimited perpetual
Failover : Active/Active perpetual
Encryption-DES : Enabled perpetual
Encryption-3DES-AES : Enabled perpetual
Security Contexts : 2 perpetual
GTP/GPRS : Disabled perpetual
AnyConnect Premium Peers : 2 perpetual
AnyConnect Essentials : Disabled perpetual
Other VPN Peers : 250 perpetual
Total VPN Peers : 250 perpetual
Shared License : Disabled perpetual
AnyConnect for Mobile : Disabled perpetual
AnyConnect for Cisco VPN Phone : Disabled perpetual
Advanced Endpoint Assessment : Disabled perpetual
UC Phone Proxy Sessions : 2 perpetual
Total UC Proxy Sessions : 2 perpetual
Botnet Traffic Filter : Disabled perpetual
Intercompany Media Engine : Disabled perpetual
Cluster : Disabled perpetual

This platform has an ASA 5510 Security Plus license.

Serial Number: xxxxxxx

Running Permanent Activation Key: 0x5e600d27 0x85b83c70 0x890d3693 0x4de3ff77 0x70429558

Configuration register is 0x41 (will be 0x1 at next reload)

Configuration last modified by enable_15 at 02:13:34.289 UTC Sun Sep 27 2020 #