

GAS GAS EC 300 R electrischestart (9 EUR)



2 MARKTPLAATS

Locatie Zuid-Holland, Giessenburg
<https://www.advertentiax.nl/x-227079-z>

GasGas EC 300R electrischestart

prijs is incl BTW en BPM

Engine
2-stroke Single-cylinder, liquid-cooled

Displacement
299,3 cc

Bore x stroke
72,0 x 72,0 mm

Starter
Electric optional



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
Gearbox 6 speed gear box with foot control
Clutch Multidisc in oil bath
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart



<https://www.advertentiax.nl/x-227079-z>
GAS GAS EC 300 R
electrischestart

Carburettor
Keihin PKWS 38 mm

Intake system
Direct reed valve VForce 4

Exhaust muffler
FMF

Bodywork
Unbreakable plastic

Handlebar
GasGas Double Force

Frame
Perimeter frame in chrome-molybdenum

Subframe
Tubular aluminum alloy

Swingarm
Aluminium, progressive system with tie rods

Front fork
Marzocchi shiver inverted ø48 mm, closed cartridge

Suspensión travel
305 mm

Adjustability
Spring preload, rebound and compression

Shock absorber
Reiger Mono shock, Special settings

Adjustability
Spring preload, rebound and compression high/low speed

Suspension travel
298 mm

Rim type
Excel Aluminium spoke rim

Rim - tyre
Front: 1.6 x 21 - Metzeler Six Days Extreme 90/90 - 21

Rim - tyre
Rear: 2.15 x 18 - Metzeler Six Days Extreme 140/80 - 18

Front brake
260 mm Galfer wave disc, 2-piston Nissin caliper

Rear brake
220 mm Galfer wave disc, 1-piston Nissin caliper

Fuel
9,5 l (2-stroke-oil/fuel mixed 1:50)

Dry weight
106 kg / 109 kg

Dimensions
Length x width x height: 2.200 x 830 x 1.260 mm

Wheelbase
1.480 mm

Seatheight
950