

Draytech Vigor 2710 series ADSL2 (0 EUR)







Locatie **Groningen, Veendam**
<https://www.advertentiax.nl/x-290321-z>

Nieuw in doos

Specificaties :

- 4 x 10/100M LAN Switch , RJ-45
- 1 x ADSL2/2+ Port, RJ-11
- 1 x FXS, RJ-11 (VDn-model) 2x FXS, RJ-11 (Vn-model)
- 1 x Line, RJ-11 (V-modellen)
- 3 x Detachable Antenna (n-modellen)
- 1 x Factory Reset Button
- 1 x Wireless on/off Button (n-modellen)
- 1 x WPS Button (n-modellen)
- 1 x USB Host 2.0
- ADSL Compliant ANSI T1.413 Issue 2
- ITU-T G.992.1 G.dmt
- ITU-T G.992.3 ADSL2 G.dmt.bis
- ITU-T G.992.5 ADSL2+
- Annex L (READSL)
- Annex M
- ATM Protocol RFC2684 MPoA (Multiple Protocol over AAL5)
- RFC2516 PPPoE (PPP over Ethernet)

 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z	 Draytech Vigor 2710 series ADSL2 https://www.advertentiax.nl/x-290321-z
---	--	--	--	---	--	--	--	--	--

G.168 Line Echo-cancellation
iLBC *
DTMF Relay In Band
Out Band (RFC-2833)
SIP Info
Supplemental Services Call Hold / Retrieve
Call Waiting
Call Waiting with Caller ID
Call Transfer
Call Forwarding (Always. Busy and No Answer)
DND (Do Not Disturb)
Call Barring (Incoming / Outgoing)
MWI (Message Waiting Indicator) (RFC-3842)
Hotline
DECT (D-modellen) Pairing up to 6 Handsets
Simultaneous Active 4 Calls
GAP / CAT-iq * Compliance
Paging Function
Wireless Access Point
(2.4GHZ) (n-modellen) IEEE802.11n Compliant
Wireless Client List
Access Point Discovery
WDS (Wireless Distribution System)
Wireless LAN Isolation
Wireless Rate Control
64/128-bit WEP
WPA/WPA2
MAC Address Access Control
WPS
Hidden SSID
WMM (Wi-Fi Multimedia)
VPN
(Specific regional variants only) 2 Concurrent VPN Tunnels
Protocol : PPP, IPSec, L2TP, L2TP over IPSec
Encryption : AES, MPPE and DES / 3DES
Authentication : MD5, SHA-1
IKE Authentication : Pre-shared Key and Digital Signature (X.509)
LAN-to-LAN, Teleworker-to-LAN
DHCP over IPSec
Dead Peer Detection (DPD)

VPN Pass-through
Firewall Multi-NAT, DMZ Host, Port-Redirection and Open Port
Object-based Firewall
MAC Address Filter
SPI (Stateful Packet Inspection)
DoS / DDoS Prevention
IP Address Anti-spoofing
E-mail Alert and Logging via Syslog
Bind IP to MAC Address
Time Schedule Control
CMS IM / P2P Applications Blocking
URL Keyword Filter (Whitelist and Blacklist)
GlobalView Web Content Filter (Powered by Commtouch)
Bandwidth Management QoS
(Specific regional variants only) Guarantee Bandwidth for VoIP
Class-based Bandwidth Guarantee by User-defined Traffic Categories
DiffServ Code Point Classifying
4-level Priority for Each Direction (Inbound/Outbound)
Bandwidth Borrowed
Bandwidth / Session Limitation
Network Feature IGMP Proxy / Snooping
DHCP Client / Relay / Server
Dynamic DNS
NTP Client
Call Scheduling
RADIUS Client
DNS Cache / Proxy
UPnP
Routing Protocol Static Routing
RIP V2
USB 3.5G USB Modem as 2nd WAN (Specific regional variants only)
Printer Sharing
File System
(throughput with above 2Mbps) Support FAT32/FAT16 File System
Support FTP Function for File Sharing
Support samba for Windows File Sharing
Network Management Web-based User Interface (HTTP / HTTPS)
Quick Start Wizard
CLI (Command Line Interface, Telnet / SSH)
Administration Access Control

Configuration Backup / Restore
Built-in Diagnostic Function
Firmware Upgrade via TFTP/FTP/WUI/TR-069
Logging via Syslog
SNMP Management MIB-II
Management Session Timeout
TR-069
2 Level Management
Temperature Operating : 0°C ~ 45°C
Storage : -25°C ~ 70°C
Humidity 10% ~ 90% (non-condensing)
Max. Power 10 Watt
Dimension L216.4 * W147.8 * H53.5 (mm)
Power DC