

CTX PV700 LCD scherm 17034 (17 EUR)



Locatie **Utrecht, Wijk bij Duurstede**
<https://www.advertentiax.nl/x-334050-z>

CTX PV700 LCD scherm 17"

Part Number:PV700

General

Packaged Quantity 1.0Display Type LCD monitor / TFT active matrixDiagonal Size 17.0 inViewable Size 17.0 inNative Resolution 1280 x 1024 at 75.0 HzPixel Pitch 0.26 mmBrightness 250.0 cd/m2Image Contrast Ratio 350:1Color Support 16.7 million colorsResponse Time 45 msVertical Refresh Rate 75 HzHorizontal Refresh Rate 82 kHzHorizontal Viewing Angle 120Vertical Viewing Angle 115Controls & Adjustments Brightness,H/V position,Dithering,Color temperature,Clock,Contrast,Phase,SmoothingOSD Languages German,Italian,French,English,SpanishFeatures AutoTuneColor BeigeDimensions (WxDxH) 17.5 in x 6.5 in x 17.5 inWeight 16.1 lbsAudioType NoneInputType None

Connectivity

Interfaces 1.0 x VGA - 15 pin HD D-Sub (HD-15)

Mechanical

Display Position Adjustments Pivot (rotation)

Miscellaneous

Features Wall mountableCompliant Standards ISO 13406-2,BSMI,DDC-2B,Plug and Play,TUV GS,CCIB,UL,TCO '99,DDC-1,cUL,FCC Class B certified

Power

Power Supply ExternalVoltage Required AC 120/230 V (50/60 Hz)Power Consumption Operational 35.0

Watt

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH

Operating Temperature 0 °F to 130 °FMaximum Storage Temperature 140 °FHumidity 5% to 90% RH



CTX PV700 LCD scherm
 17034




CTX PV700 LCD scherm
 17034




CTX PV700 LCD scherm
 17034



CTX PV700 LCD scherm
 17034




CTX PV700 LCD scherm
 17034



CTX PV700 LCD scherm
 17034



CTX PV700 LCD scherm
 17034



CTX PV700 LCD scherm
 17034



CTX PV700 LCD scherm
 17034



CTX PV700 LCD scherm
 17034

<https://www.advertentiax.nl/x-334050-z>