

MPC 15034 Panel PC with Resistive Touch Screen (295 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentieX.nl/x-353283-z>

MPC 15" Panel PC with Resistive Touch ScreenA Touch Panel PC is an advanced metal Panel PC. It is ultra slim and exquisite metal enclosure catches most eye contacts. This series is equipped with high brightness TFT panel and Touch screen.Motherboard

CPU: Intel Celeron M 1.0 GHz (supports 1.5 GHz and Pentium M 1.8 GHz)

Chipset: Intel 852GM and ICH4 FSB 400Mhz

System Memory: 512MB, 1x DDR SODIMM slot, up to 2GB

Graphic Memory: Shared system memory

LCD/Touch Panel LCD size: 15"

Brightness (cd/m2): 350

Maximal resolution: 1024 x 768

Contrast Ratio: 400:1



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>




MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen
 Lamp lifetime (hrs): 50000
 Touch screen type: Resistive Touch
 Storage
 HDD: 2.5" 40GB

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>




MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>



MPC 15034 Panel PC with Resistive Touch Screen

<https://www.advertentieX.nl/x-353283-z>

External I/O ports

USB ports:4 x

Serial/COM ports:COM1 standard RS-232, COM2 RS-232/422/485 by jumper
COM3/COM4 pin 9 with 5V/12V power by jumper

LAN:10/100Mb RJ-45

Audio:1 x line-out, 1 x line-in, 2 x speaker 3W

Power Adapter: 19V 90W

Environment

EMC & Safety:CE, FCC Class A, LVD

Operating Temperature:0° ~ 40° C

Storage Temperature:-20° ~ 60° C

Operating Humidity:5% - 95% RH, non condensing

Storage Humidity:5% - 95% RH, non condensing

Dimension (WxHxD):386 x 308 x 60 mm

Mounting:100 x 100 mm VESA

OS Support:

Windows 9x/ME,
Windows NT 4.0,
Windows 2000,
Windows XP, Windows 7
CE 4.2/5.0,
0174708552