

Apple Xserve 2009 (275 EUR)













Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiax.nl/x-504393-z>

Te koop:

Apple Xserve 2009 in goede staat, zeer weinig belast.
Geen software bijgeleverd. Ondersteunt OSX Yosemite!

Xserve (2009) - Technical Specifications

Processor
One 2.26GHz Quad-Core Intel Xeon 5500 series "Nehalem" processor
8MB shared L3 cache per processor
Three-channel integrated memory controller per processor
Hyper-Threading support with two threads per core (up to 16 virtual cores)
Turbo Boost for increased performance under dynamic workloads (up to 3.33GHz on a 2.93GHz processor)
QuickPath Interconnect
128-bit SSE4 SIMD engine
64-bit data paths and registers
Energy efficiency optimization

 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009	 https://www.advertentiax.nl/x-504393-z Apple Xserve 2009
--	---	---	---	--	---	---	---	---	---

Support for reading SMART data from Apple Drive Modules for prefailure notification

8x SuperDrive DL (DVD±R DL/DVD±RW/CD-RW)

I/O connections

Two open PCI Express 2.0 x16 expansion slots: one half-length (6.6-inch) and one 9.25-inch length

Two independent 10/100/1000BASE-T (Gigabit) RJ-45 Ethernet interfaces with support for jumbo frames

Two FireWire 800 ports on back panel; 15W total power

Two USB 2.0 ports (480Mb/s each) on back panel; and one USB 2.0 port on front panel

One DB-9 serial port (RS-232)

Video and graphics support

NVIDIA GeForce GT 120 graphics with 256MB of GDDR3 memory and Mini DisplayPort output

VGA output using Mini DisplayPort to VGA Adapter (sold separately)

DVI output using Mini DisplayPort to DVI Adapter (sold separately)

Rack support

Fits EIA-310-D-compliant, industry-standard four-post racks and cabinets: 19 inches wide, 24 to 36 inches deep

Front-to-back cooling for rack enclosure

Support for square-hole racks or threaded racks based on mounting kit selection

Electrical requirements

Output power: 750W

Optional second load-sharing 750W power supply for redundancy

Line voltage: universal input (100V to 240V AC), power factor corrected

Maximum input current: 8.0A (100V to 120V) or 4.0A (200V to 240V); current is shared when system is configured with two power supplies

Frequency: 50Hz to 60Hz, single phase

Environmental requirements

Operating temperature: 50° to 95° F

(10° to 35° C)

Storage temperature: 40° to 116° F

(40° to 47° C)

Relative humidity: 5% to 95% noncondensing

Maximum altitude: 10,000 feet

FCC Class A approved

Size and weight

Height: 1.73 inches (4.4 cm)

Width: 17.6 inches (44.7 cm) for mounting in standard 19-inch rack

Depth: 30 inches (76.2 cm)

Weight: 30.8 pounds (14.0 kg) base configuration; 38.3 pounds (17.4 kg) for 8-core system with twelve DIMMs, three 1TB SATA Apple Drive Modules, and two power

