3com gigabit Baseline Switch 2948-SFP Plus - 3CBLSG48 (100 EUR)



Locatie Noord-Holland, Amsterdam

https://www.advertentiex.nl/x-504453-z

48 poorts web managed Gigabit Switch in nette staat. Meerdere beschikbaar.

Specificaties:

Affordable, Managed Gigabit Switching with Flexible Uplinks

The "smart" voice-ready 3Com Baseline Switch 2948-SFP Plus is a web-managed Layer 2 Gigabit switch. It offers enterprise-class features, customized and priced for small- and mid-sized organizations.

With an easy-to-use switch interface and advanced features (VLANs, IEEE 802.1X authentication and Rapid Spanning Tree), this switch is the most cost-effective way to provide a converged network.

Layer 2 Switching with Advanced Features

The Baseline Switch 2948-SFP Plus has forty-eight 10/100/1000 ports and four dual-purpose Gigabit ports (copper or SFP-based fiber) to connect to high-performance computers, servers, or core network backbones.

This "smart" switch has the features that help build a voice ready network, with support for auto-voice VLAN, SNMP-based management, IGMP snooping and guery, and IEEE 802.1X and advanced Access Control Lists (ACLs) for strengthening security.



https://www.advertentiex.nl/x-5044 53-z



https://www.advertentiex.nl/x-5044 gigabit Baseline FP Plus - 3CE



ကြောင်းizations prigrify and vicality and v bandwidth as traffic flow is diested according to the needs of the business No Switch Setup Reguired No Switch Setup Required | Setup Require

agceptable, here is go need to configure the switch. If desged, the switch care be configured using a seline Switch 3CBLSG48









browser or SNMP management software

Producteigenschappen van 3Com 3CBLSG48 Baseline 2948-SFP Plus

- . Ports
- . 48 autosensing 10/100/1000 ports; 4 Gigabit SFP ports, dual-purposed with 4 of the 10/100/1000 ports
- . Performance
- . 96 Gbps, max.; wirespeed performance across ports
- . Layer 2 switching
- . full-rate nonblocking on all ports, full-/half-duplex autonegotiation, flow control,
- . IEEE 802.1Q VLAN support, IEEE 802.1p traffic prioritization, IGMP snooping; more
- . Convergence
- . 4 hardware queues per port; traffic prioritization at Layer 2 (802.1p) and at Layer 3 (TOS with DSCP);
- . auto-VLAN assignment for voice traffic; more
- . Security
- . IEEE 802.1X network login; advanced ACLs
- . Switch management
- . Web-based configuration, 3Com Network Supervisor and Network Director, other SNMP management tools:
- . CLI using console port
- . Dimensions
- . height 4.4 cm (1.7 in or 1 RU); width 44.0 cm (17.3 in); depth 23.8 cm (9.4 in)
- . Weight: 2.5 kg (5.5 lb)
- . Package Contents
- . switch unit
- . power cord
- . self-adhesive rubber pads
- . console cable
- . rack-mount kit
- . product CD
- warranty and safety information 0306921574