

24 x Vetpatroon EP-2 Multi-MoS2 400 Gr. per stuk 2,50 Excl (2,50 EUR)



Locatie **Noord-Brabant, Heerle**
<https://www.advertentieX.nl/x-534876-z>

Te Koop Rechtstreek van de Importeur :

24 x Vetpatroon EP-2 Multi-MoS2 - 400 Gr.

Prijs per 24 stuks Slechts € 2,50 Excl. BTW PER STUK / ABSOLUT TOPKWALITEIT GREASE!!!

Specificatie als volgt :

Nummer 8103

Vetpatroon

Super Kwaliteit Duits Product

Universal Multi-MoS2 Grease EP2 (KPF2K-30) is an extraordinary ageing stable, lithium based fat with excellent corrosion prevention qualities. The grease is made of high-quality basic oil and uses additives like molybdenum disulfide to improve emergency run qualities, corrosion prevention and pressure durability. Mannol Universal Multi-MoS2 Grease EP2 is a multipurpose grease, formulated for all lubrication places in vehicles, construction machines, agricultural machinery and mechanical engineering. This grease is particularly suitable for rolling and sliding bearings and joint lubrication with slow and/or

oscillating movements. The operating temperature range of Mannol Universal Multi-MoS2 Grease EP2

is -30°C to +130°C

1. Short Name DIN 51502 KPF2K-30

2. Colour Black

3. Working Temperature °C -30 to 130

4. Dropping Point GB/T4929 °C 190

5. NLGI Class 2

6. ASTM Worked Penetration GB/T269 mm/10min 265-295

7. Soap Lithium

8. Colour Black

9. Working Temperature °C -30 to 130

10. Dropping Point GB/T4929 °C 190

11. NLGI Class 2

12. ASTM Worked Penetration GB/T269 mm/10min 265-295

13. Soap Lithium

14. Colour Black

15. Working Temperature °C -30 to 130

16. Dropping Point GB/T4929 °C 190

17. Short Name DIN 51502 KPF2K-30

18. Colour Black

19. Working Temperature °C -30 to 130

20. Dropping Point GB/T4929 °C 190

21. NLGI Class 2

22. ASTM Worked Penetration GB/T269 mm/10min 265-295

23. Soap Lithium

24. Colour Black

25. Working Temperature °C -30 to 130

26. Dropping Point GB/T4929 °C 190

27. NLGI Class 2

28. ASTM Worked Penetration GB/T269 mm/10min 265-295

29. Soap Lithium

30. Colour Black

31. Working Temperature °C -30 to 130

32. Dropping Point GB/T4929 °C 190

33. NLGI Class 2

34. Short Name DIN 51502 KPF2K-30

35. Colour Black

36. Working Temperature °C -30 to 130

37. Dropping Point GB/T4929 °C 190

38. NLGI Class 2

39. ASTM Worked Penetration GB/T269 mm/10min 265-295

40. Soap Lithium

41. Colour Black

42. Working Temperature °C -30 to 130

43. Dropping Point GB/T4929 °C 190

44. NLGI Class 2

45. ASTM Worked Penetration GB/T269 mm/10min 265-295

46. Soap Lithium

47. Colour Black

48. Working Temperature °C -30 to 130

49. Dropping Point GB/T4929 °C 190

50. NLGI Class 2

51. Short Name DIN 51502 KPF2K-30

52. Colour Black

53. Working Temperature °C -30 to 130

54. Dropping Point GB/T4929 °C 190

55. NLGI Class 2

56. ASTM Worked Penetration GB/T269 mm/10min 265-295

57. Soap Lithium

58. Colour Black

59. Working Temperature °C -30 to 130

60. Dropping Point GB/T4929 °C 190

61. NLGI Class 2

62. ASTM Worked Penetration GB/T269 mm/10min 265-295

63. Soap Lithium

64. Colour Black

65. Working Temperature °C -30 to 130

66. Dropping Point GB/T4929 °C 190

67. NLGI Class 2

68. Short Name DIN 51502 KPF2K-30

69. Colour Black

70. Working Temperature °C -30 to 130

71. Dropping Point GB/T4929 °C 190

72. NLGI Class 2

73. ASTM Worked Penetration GB/T269 mm/10min 265-295

74. Soap Lithium

75. Colour Black

76. Working Temperature °C -30 to 130

77. Dropping Point GB/T4929 °C 190

78. NLGI Class 2

79. ASTM Worked Penetration GB/T269 mm/10min 265-295

80. Soap Lithium

81. Colour Black

82. Working Temperature °C -30 to 130

83. Dropping Point GB/T4929 °C 190

84. NLGI Class 2

85. Short Name DIN 51502 KPF2K-30

86. Colour Black

87. Working Temperature °C -30 to 130

88. Dropping Point GB/T4929 °C 190

89. NLGI Class 2

90. ASTM Worked Penetration GB/T269 mm/10min 265-295

91. Soap Lithium

92. Colour Black

93. Working Temperature °C -30 to 130

94. Dropping Point GB/T4929 °C 190

95. NLGI Class 2

96. ASTM Worked Penetration GB/T269 mm/10min 265-295

97. Soap Lithium

98. Colour Black

99. Working Temperature °C -30 to 130

100. Dropping Point GB/T4929 °C 190

101. NLGI Class 2

102. Short Name DIN 51502 KPF2K-30

103. Colour Black

104. Working Temperature °C -30 to 130

105. Dropping Point GB/T4929 °C 190

106. NLGI Class 2

107. ASTM Worked Penetration GB/T269 mm/10min 265-295

108. Soap Lithium

109. Colour Black

110. Working Temperature °C -30 to 130

111. Dropping Point GB/T4929 °C 190

112. NLGI Class 2

113. ASTM Worked Penetration GB/T269 mm/10min 265-295

114. Soap Lithium

115. Colour Black

116. Working Temperature °C -30 to 130

117. Dropping Point GB/T4929 °C 190

118. NLGI Class 2

119. Short Name DIN 51502 KPF2K-30

120. Colour Black

121. Working Temperature °C -30 to 130

122. Dropping Point GB/T4929 °C 190

123. NLGI Class 2

124. ASTM Worked Penetration GB/T269 mm/10min 265-295

125. Soap Lithium

126. Colour Black

127. Working Temperature °C -30 to 130

128. Dropping Point GB/T4929 °C 190

129. NLGI Class 2

130. ASTM Worked Penetration GB/T269 mm/10min 265-295

131. Soap Lithium

132. Colour Black

133. Working Temperature °C -30 to 130

134. Dropping Point GB/T4929 °C 190

135. NLGI Class 2

136. Short Name DIN 51502 KPF2K-30

137. Colour Black

138. Working Temperature °C -30 to 130

139. Dropping Point GB/T4929 °C 190

140. NLGI Class 2

141. ASTM Worked Penetration GB/T269 mm/10min 265-295

142. Soap Lithium

143. Colour Black

144. Working Temperature °C -30 to 130

145. Dropping Point GB/T4929 °C 190

146. NLGI Class 2

147. ASTM Worked Penetration GB/T269 mm/10min 265-295

148. Soap Lithium

149. Colour Black

150. Working Temperature °C -30 to 130

151. Dropping Point GB/T4929 °C 190

152. NLGI Class 2

153. Short Name DIN 51502 KPF2K-30

154. Colour Black

155. Working Temperature °C -30 to 130

156. Dropping Point GB/T4929 °C 190

157. NLGI Class 2

158. ASTM Worked Penetration GB/T269 mm/10min 265-295

159. Soap Lithium

160. Colour Black

161. Working Temperature °C -30 to 130

162. Dropping Point GB/T4929 °C 190

163. NLGI Class 2

164. ASTM Worked Penetration GB/T269 mm/10min 265-295

165. Soap Lithium

166. Colour Black

167. Working Temperature °C -30 to 130

168. Dropping Point GB/T4929 °C 190

169. NLGI Class 2

170. Short Name DIN 51502 KPF2K-30

171. Colour Black

172. Working Temperature °C -30 to 130

173. Dropping Point GB/T4929 °C 190

174. NLGI Class 2

175. ASTM Worked Penetration GB/T269 mm/10min 265-295

176. Soap Lithium

177. Colour Black

178. Working Temperature °C -30 to 130

179. Dropping Point GB/T4929 °C 190

180. NLGI Class 2

181. ASTM Worked Penetration GB/T269 mm/10min 265-295

182. Soap Lithium

183. Colour Black

184. Working Temperature °C -30 to 130

185. Dropping Point GB/T4929 °C 190

186. NLGI Class 2

187. Short Name DIN 51502 KPF2K-30

188. Colour Black

189. Working Temperature °C -30 to 130

190. Dropping Point GB/T4929 °C 190

191. NLGI Class 2

192. ASTM Worked Penetration GB/T269 mm/10min 265-295

193. Soap Lithium

194. Colour Black

195. Working Temperature °C -30 to 130

196. Dropping Point GB/T4929 °C 190

197. NLGI Class 2

198. ASTM Worked Penetration GB/T269 mm/10min 265-295

199. Soap Lithium

200. Colour Black

201. Working Temperature °C -30 to 130

202. Dropping Point GB/T4929 °C 190

203. NLGI Class 2

204. Short Name DIN 51502 KPF2K-30

205. Colour Black

206. Working Temperature °C -30 to 130

207. Dropping Point GB/T4929 °C 190

208. NLGI Class 2

209. ASTM Worked Penetration GB/T269 mm/10min 265-295

210. Soap Lithium

211. Colour Black

212. Working Temperature °C -30 to 130

213. Dropping Point GB/T4929 °C 190

214. NLGI Class 2

215. ASTM Worked Penetration GB/T269 mm/10min 265-295

216. Soap Lithium

217. Colour Black

218. Working Temperature °C -30 to 130

219. Dropping Point GB/T4929 °C 190

220. NLGI Class 2

221. Short Name DIN 51502 KPF2K-30

222. Colour Black

223. Working Temperature °C -30 to 130

224. Dropping Point GB/T4929 °C 190

225. NLGI Class 2

226. ASTM Worked Penetration GB/T269 mm/10min 265-

Ook andere onderhoudsmiddelen op voorraad tegen absolute bodemprijzen!!

Afhalen is alleen op afspraak mogelijk Tel.06-54-294549

Bestellen is ook eenvoudig via onze WEBSHOP mogelijk.

Handelsonderneming Nemeco

Jagersweg 2a

4726SL Heerle (Tussen Roosendaal en Bergen op Zoom)

Tel.06-54-294549

Toon telefoonnummer