

Netgear Prosafe SRX5308 (150 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiex.nl/x-541546-z>

Netgear Prosafe SRX5308 router. 4 x WAN poorten en 4x LAN poorten. Ideaal voor fail-over verbindingen of VPN netwerken.



PERFORMANCE

LAN-to-WAN Throughput1: 924 Mbps

IPsec VPN (3DES) Throughput1: 180 Mbps

SSL VPN Throughput1 21 Mbps

Maximum Concurrent Connections: 200,000

Maximum Number of VLANs: 254

Dedicated IPsec VPN Tunnels: 125

FIREWALL FEATURES



Stateful Packet Inspection (SPI)

Port/Service Blocking, Denial-of-service (DoS) Prevention, Stealth Mode, Block TCP Flood, Block UDP Flood, WAN/LAN Ping

Response Control

Firewall Functions

Port Range Forwarding, Port Triggering, DNS proxy, MAC Address Cloning/spoofing, NTP Support,

 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z	 Netgear Prosafe SRX5308 https://www.advententix.nl/x-5415-46-z
--	--	--	--	--	--	--	--	--

Key Exchange: IKE, Manual Key, Pre-shared Key, PKI, X.509 v3
IPsec Access Modes: Client-to-site, Site-to-site
SSL Version Support: SSLv3, TLS1.0
SSL Encryption Support: DES, 3DES, ARC4, AES(ECB, CBC, XCBC, CNTR)128, 256 bit
SSL Message Integrity: MD5, SHA-1, MAC-MD5/SHA-1, HMAC-MD5/SHA-1
SSL Certificate Support: RSA, Diffie-Hellman, Self
SSL VPN Platforms Supported: Windows 2000/XP/Vista/Windows 7 (32, 64 bit), MAC OS X 10.4+

MANAGEMENT

Management Interface Options: HTTP/HTTPS, SNMP v2c, Telnet
Logging: Accepted Packets, Dropped Packets, System, Source MAC filter, Session Limit, Bandwidth Limit, SSI VPN,
IPsec VPN
Log Delivery: Email Delivery, Syslog
Diagnostics: Ping, DNS Lookup, Trace Route
Maintenance: Save/restore Configuration, Restore to Factory Defaults, Firmware Upgrades via Web Browser, Display
Statistics

HARDWARE

Gigabit RJ45 Ports WAN/LAN: 4/4
DMZ Interfaces (Configurable): 1
Flash Memory/RAM: 64 MB/512 MB
Certifications: VPNC (Basic, AES Interop)
Major Regulatory Compliance: Environment: RoHS, China RoHS Safety: CE/LVD, cUL EMI: FCC Part 15 Class A, CE mark
commercial, C-Tick Class A, VCCI
Storage and Operating Temperatures:
Operating Temperature: 0° - 45°C (32°-113° F)
Storage Temperature: -20° - 70° C (-4° - 158° F)
Humidity: Operation 90% Maximum Relative, Storage 95% Maximum Relative
Electrical Specifications: AC 100-240V, 50/60 Hz Universal Input, DC 5V/5A Output Internal Power Supply
Dimensions (W x H x D) cm: 33 x 4.3 x 20.9
Weight: kg 2.1
System Requirements: Cable, DSL, or Wireless Broadband Modem, Internet Service, Network Card for Each Connected
PC, Network Software (e.g. Windows), Internet Explorer 5.0 or Higher or Mozilla Firefox 1.0 or Higher
Package Contents: ProSafe Quad WAN Gigabit Firewall (SRX5308), Ethernet Cable, Power Cable, Rackmount Kit, Rubber

Feet, Installation Guide, Warranty/Support Information Card, Resource CD With Single User ProSafe
VPN Client Software
License
Warranty: