

CTX PV700 LCD scherm 17034 (19,95 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentienx.nl/x-562468-z>

CTX PV700 LCD scherm 17"

General

Part Number:PV700Packaged Quantity 1.0Display Type LCD monitor / TFT active matrixDiagonal Size 17.0 inViewable Size 17.0 inNative Resolution 1280 x 1024 at 75.0 HzPixel Pitch 0.26 mmBrightness 250.0 cd/m2Image Contrast Ratio 350:1Color Support 16.7 million colorsResponse Time 45 msVertical Refresh Rate 75 HzHorizontal Refresh Rate 82 kHzHorizontal Viewing Angle 120Vertical Viewing Angle 115Controls & Adjustments Brightness,H/V position,Dithering,Color temperature,Clock,Contrast,Phase,SmoothingOSD Languages German,Italian,French,English,SpanishFeatures AutoTuneColor BeigeDimensions (WxDxH) 17.5 in x 6.5 in x 17.5 inWeight 16.1 lbsAudioType NoneInputType None

Connectivity

Interfaces 1.0 x VGA - 15 pin HD D-Sub (HD-15)

Mechanical

Display Position Adjustments Pivot (rotation)

Miscellaneous

Features Wall mountableCompliant Standards ISO 13406-2,BSMI,DDC-2B,Plug and Play,TUV GS,CCIB,UL,TCO '99,DDC-1,cUL,FCC Class B certified

Power

Power Supply ExternalVoltage Required AC 120/230 V (50/60 Hz)Power Consumption Operational 35.0



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>




CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>




CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>



CTX PV700 LCD scherm
 17034

<https://www.advertentienx.nl/x-562468-z>

Watt

Operating Temperature 0 °C to 40 °C
 Storage Temperature -20 °C to 60 °C
 Humidity 10% to 90% RH
 Shock 1000g
 Vibration 10g
 ESD 1000V
 RoHS Compliant