



Zeer mooie Harley Davidson Fatboy FLSTFB special uit 2011 met slechts 5320 originele kilometers op de teller en uitgevoerd in een schitterende matzwarte kleur (black denim)

Hij is nog fabriek-af origineel en alle papieren aanwezig.

De kenner behoeft geen verder uitleg!

LET OP: dit is een vaste prijs.....i.v.m vertrek naar buitenland nu van € 16.800,-.....voor € 15.500,- (deze prijs is niet meer onderhandelbaar)

Kenmerken:

Bouwjaar : 2011

Kilometerstand : 5320

Motorinhoud : 1584 (76 pk)

Nieuwprijs : € 23.995,-



Artex® Cleaner Paper, washable,

Harley Davidson Fat boy
FLSTFB special, Black denim
5320 KM
<https://www.advertentiax.nl/x-6350>
54-z

Harley Davidson Fat boy
FLSTFB special, Black denim
5320 KV

Lubrication System Pressurized, dry-sump

Drivetrain

Primary Drive Chain, 34/46 ratio

Final Drive 6 Belt, 32/66 ratio

Clutch Multi-plate, wet

Transmission 6-Speed Cruise Drive®

U.S. Gear Ratios (overall):

- o 1st 9.311

- o 2nd 6.454

- o 3rd 4.793

- o 4th 3.882

- o 5th 3.307

- o 6th 2.790

Chassis

Frame Mild steel tubular frame; rectangular section backbone; stamped, cast, and forged junctions; forged fender supports; MIG welded

Swingarm Mild steel, round tube sections, forged junctions; MIG welded

Front Forks 41.30 mm telescopic, "beer can" covers

Rear Shocks Hidden, horizontal-mounted, coil-over

Wheels 7: Black, Bullet Hole Disc Cast Aluminum

- o Front 17 in. x 3.50 in. (431.80 mm x 88.90 mm)

- o Rear 17 in. x 6 in. (431.80 mm x 152.40 mm)

Brakes:

- o Caliper Type 4-piston front and 2-piston rear

- o Rotor Type (diameter x width): Patented, uniform expansion rotors

- o Front 11.50 in. x .20 in. (292.10 mm x 5.08 mm)

- o Rear 11.50 in. x .23 in. (292.10 mm x 5.84 mm)

Suspension Travel:

- o Front Wheel 5.10 in. (129.54 mm)

- o Rear Wheel 3.60 in. (91.44 mm)

Performance

Engine Torque (per SAE J1349):

- o North America 93.67 ft. lbs. @ 3000 rpm (127.0 Nm @ 3000 rpm)

Lean Angle (per SAE J1168):

- o Right 25.6°

- o Left 25.2°

Fuel Economy

(EPA urban/highway test) 35/54 mpg (6.72/4.36 L/100 km)

Electric

Battery (per Battery Council International Rating) Sealed, maintenance-free, 12V, 19-amp/hour, 270 cca

Charging Three-phase, 38-amp system (439W @ 13V, 2000 rpm, 489W max power @ 13V)

Starting 1.2 kW electric with solenoid shift starter motor engagement

Lights (as per country regulation):

- o Headlamp (quartz halogen) 55-watt low beam, 60-watt high beam

- o Tail/Stop Lights 8W/28W (5W/21W)

- o Turn Signal Lights 28W (21W) self-canceling

- o Indicator Lamps High beam, neutral, low oil pressure, turn signals, engine diagnostics, security system8 (optional), 6-speed, low fuel warnings

Dimensions

Length 94.30 in. (2395.22 mm)

Overall Width 39.20 in. (995.68 mm)

Overall Height 44.30 in. (1125.22 mm)

Seat Height:

- o Laden2 24.25 in. (615.95 mm)

- o Unladen 26.35 in. (669.29 mm)

Ground Clearance 4.80 in. (121.92 mm)

Rake (steering head) 31.6°

Fork Angle 31.6°

Trail 5.80 in. (147.32 mm)

Wheelbase 64.50 in. (1638.30 mm)

Tires (Dunlop® Harley-Davidson Series, radial blackwall front and rear):

- o Front - D408F 140/75R17 67V

- o Rear - D407 200/55R17 78V

Fuel Capacity 5 gal. (18.93 L) (warning light at approximately 1 gal.)

Oil Capacity (w/filter) 3.50 qts. (3.31 L)

Transmission Capacity 1 qts. (0.95 L)

Primary Chain Case Capacity3 1 qts. (0.95 L)

Weight:

- o As Shipped 700 lbs. (317.52 kg)

- o In Running Order 731.25 lbs. (331.70 kg)

-
- o Gross Vehicle Weight Rating 1160 lbs. (526.18 kg)
 - o Gross Axle Weight Rating:
 - o Front 430 lbs. (195.05 kg)
 - o Rear 730 lbs. (331.13)