

Cisco 828 G.SHDSL 47-15807-01 REV A1 DPH Router met Adapter (15 EUR)



Locatie

Noord-Holland, Amsterdam

<https://www.advertentieX.nl/x-692514-z>

Cisco 828 G.SHDSL 47-15807-01 REV A1 DPH Router met AdapterCisco 800 Series

2461B-0006*

Manufacturer Part # CISCO828-RF

Aansluitingen

4x 10Mb LAN

1x SHDSL

1x Console

Meegeleverd

- originele cisco adapter (voeding)
- G.SHDSL kabel
- 5x UTP kabels

Verzenden 7,50€

Specifications

General* Enclosure Type - Desktop - modular

https://www.advertentieX.nl/x-6925														
Cisco 828 G.SHDSL Router met Adapter	Cisco 828 G.SHDSL Router met Adapter													
47-15807-01 REV A1 DPH	47-15807-01 REV A1 DPH													
Router met Adapter	Router met Adapter	Router met Adapter												



Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

Cisco 828 G.SHDSL Router met Adapter

47-15807-01 REV A1 DPH

Router met Adapter

https://www.advertentieX.nl/x-6925

TCP/IP Features
CHAP authentication, IP-routing, NAT support, PAP authentication, Triple DES, manageable, routing, scalable clustering

Compliant Standards
IEEE 802.3

Remote Management Protocol
HTTP, SNMP

Data Transfer Rate
10 Mbps

Modem*
Type: modem

Max Transfer Rate
2.3 Mbps

Digital Signaling Protocol
SHDSL

Power Device*
Voltage Required: AC 110/220 V

Frequency Required
50/60 Hz

Type
internal power supply

Camera*
Installed Size
8 MB

Processor*
Clock Speed
50 MHz

Interface Provided*
Gender
female, female, female

Connector Qty
1, 1

Type
management, modem,

networkInterface
Ethernet 10Base-T, SHDSL, console

Connector Type
RJ-45, RJ-45, RJ-45

WAN / DMZ

WAN

Telecom*
Compliant Standards
ITU G.991.2 (G.shdsl)

Dimensions & Weight*
Depth 8.3 in
Width 9.7 in
Height 2 in
Weight 1.54