

3000watt kicker sound (1.250 EUR)



Locatie Zuid-Holland, s-Gravenhage
<https://www.advertentiax.nl/x-716325-z>

Complete Kicker Sound 3000watt...

Nieuwprijs in winkel boven 2500euro

- 3x kicker cvx10
- 1x kicker zx2500.1
- 1x kicker sx400.2
- 1x toxic tox-3000
- 1x impulse

KICKER CVX10
Subwoofer Size 10"
Dual 2 Ohm Voice Coils
Peak Power Handling 1200 watts
RMS Power Handling 600 watts
Woofer Surround Santoprene rubber
Sealed Box Volume 0.8 - 3.0 cubic feet
Ported Box Volume 1.25 - 1.75 cubic feet

 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound	 https://www.advertentiax.nl/x-716325-z 3000watt kicker sound
---	--	--	--	---	--	--	--	--	--

indicator featuring a new flashing yellow low-voltage light enhances the end panel

Bridgeable operation

Preamp RCA outputs

Automatic turn on modes: remote, DC offset, or signal sense

Thermal, voltage, and short circuit protection circuitry

Variable low-pass filter (50-200 Hz, 24 dB/octave)

Subsonic Filter (24 dB at 25 Hz)

CEA-2006 compliant amplifier

Frequency response: 25-200 Hz

KICKER SX400.2

100 watts x 2 channels @ 4 ohms

200 watts x 2 channels @ 2 ohms

400 watts x 1 channel @ 4 ohms BridgedUltraMatchGain Structure, single-band parametric KickEQ

Variable Gain, Boost, and Q, and crossoversÂ Variable High and Low-Pass Filters

SAMS (Stereo And Mono Simultaneously)

ISIS (Indicate Status & Input Settings) Interface

SORT Protection Circuitry (Short Circuit, Over-Voltage, Reverse Polarity, Thermal)

BLASTPort (Bass Level And Signal Transfer) Provides Remote Bass LevelControl and control signal transfer between multiple SX amplifiers

Kompressor

Adjustable Phase Control: 0 - 180

EndKaps: Cast aluminum, custom, removable covers to protect and hide all your wiring connections to the amplifier

Amp Strapping lets you put two mono amplifiers together into a single unit with double the power.

SickBay and On Board Diagnostics

Left and right channels can be adjusted together or separately.

Frequency Response: 20 Hz - 200 kHz

Remote Gain Control with 20' cord

Variable Input Sensitivity: 1V / 2V / 4V / 8V / 16V

Signal-to-Noise Ratio: >100 dB

MOSFET Power Supply

RCA Outputs: 1 Pair

Fan Cooling

VOOR MEER INFO GRAAG...