

Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) (50 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiex.nl/x-736339-z>



Zie foto's



In goede staat, gereset (dus geen wachtwoord)
 Zonder harddisks

Het is een Transtec PV620S16R1A (Provigo 620 ?)
 Volgens mij is dit een rebrand van een Infotrend Eonstor U16U-G4020

Info die ik op LCD scherm lees:

- PV620S16R1A
- Firmware 3.47A.07
- 2048mb ddr ecc
- PPC750FX / Powerpc 750fx processor

Incl BBU battery backup unit
 16 bay hot swappable
 Incl 2x rs232 port via audiojack en 1x ethernet LAN
 Configuratie kan ook via knoppen bij lcdschermpje op de voorkant
 2x externe SCSI 320 poorten IN
 2x externe SCSI 320 poorten OUT

 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z	 Transtec 16 bay NAS SCSI RAID server (Infotrend Eonstor) https://www.advertentiex.nl/x-736339-z
---	--	--	--	---	--	--	--	--	--

on array sizes.

Configuration Model Form Factor Single U16U-G4020 3U Specifications RAID

Multiple arrays configurable with dedicated or global hot sparesRAID levels supported: RAID 0, 1 (0+1), 3, 5, 10, 30, 50, and NRAID

Interfaces

Two (2) dual-stacked VHDCI SCSI portsTwo (2) audio jack RS-232C serial port (38400, n, 8, 1)One (1) 10/100M Ethernet port

Power Supply Module Two (2) redundant hot-swappable power supplies with PFC

Input: 100VAC at 10A, 240VAC at 5A with PFC (auto-switching) 47 ~ 63Hz

Output: (Maximum output: 460 Watts)

+12.0V 23A max.

+ 5.0V 32A max.

+ 3.3V 30A.