

Dell Wyse V90LE 1.2GHz 1G 1G XPE 902144-08L thin client (79,95 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiex.nl/x-776120-z>

Dell Wyse V90LE 1.2GHz 1G 1G XPE 902144-08L thin client

Windows XP embedded operating system, 1.2GHZ VIA Eden processor x1, 1GB Flash installed- 2GB max, 1GB DDR II SDRAM installed- 1 GB max, Versatile form factor, Includes PCMCIA Slot, up to 1920x1080 display resolution, 1 DVI-I (VGA converter cable included), DVI-I splitter cable is required for dual video (splitter cable is sold separately P/N 920302-92L), 3 USB v2.0, 1 Serial, 1 Parallel, 2 PS/2, 10/100BaseT, Dimensions (WxDxH) 4.6 cm x 18 cm x 20.1 cm, Weight, 3.6 kg, Hard Drive None. Monitor None. Audio Output, Sound card - stereo, Network adapter - Ethernet, Fast Ethernet, Power AC 120/230 V (50/60 Hz).

Specs

Processor

Frequentie van processor * 1,2 GHz
Processorfamilie VIA C7A
Aantal processorkernen 1

Opslagmedia

Totale opslagcapaciteit * 1 GB Opslagmedia * FlashGeïntegreerde geheugenkaartlezer * Yes

Geheugen

Intern geheugen * 1 GBIntern geheugentype * DDR2-SDRAMMaximum intern geheugen 1 GB

Video


Maximum resolutie 1920 x 1080 Pixels

Network

Wi-Fi * YesWi-Fi-standaarden 802.11b, 802.11gEthernet LAN * YesBekabelingstechnologie 10/100Base-



Dell Wyse V90LE 1.2GHz 1G
1G XPE 902144-08L thin client




Dell Wyse V90LE 1.2GHz 1G
1G XPE 902144-08L thin client



Dell Wyse V90LE 1.2GHz 1G
1G XPE 902144-08L thin client



Dell Wyse V90LE 1.2GHz 1G
1G XPE 902144-08L thin client



Dell W550 V0LE 1.2GHz 1GB
15 XPE 902144-08L thin client



Cell wise VOLTE 1.2GHz 1G
15 XPE 902154-08L thin client




Intel® Xeon® E5-2680 v4 2.4GHz 14-core 35MB cache
16GB DDR4-2133 ECC
15 XPE.9021134-08L thin client




Dell Wse Vole 1.2GHz 1G
 1G XPE 902114408L thin client



bell mouse V90LE 1.2GHz 1G
1S XPE 90214408L thin client
17,2
VCC



Dell Wyse V90LE 1.2GHz 1G
1G XPE 902144-08L thin client

 Poorten & Interfaces SmartCard slot Yes (S/2 poorten) 2 Design Rack-montage Yes Energie Afvoer voltage 180-240 VAC Certificering cULus 60950, TAA	 Poorten & Interfaces SmartCard slot Yes (S/2 poorten) 2 Design Rack-montage Yes Energie Afvoer voltage 180-240 VAC Certificering cULus 60950, TAA	 Poorten & Interfaces SmartCard slot Yes (S/2 poorten) 2 Design Rack-montage Yes Energie Afvoer voltage 180-240 VAC Certificering cULus 60950, TAA	 Poorten & Interfaces SmartCard slot Yes (S/2 poorten) 2 Design Rack-montage Yes Energie Afvoer voltage 180-240 VAC Certificering cULus 60950, TAA	 Poorten & Interfaces SmartCard slot Yes (S/2 poorten) 2 Design Rack-montage Yes Energie Afvoer voltage 180-240 VAC Certificering cULus 60950, TAA	 Poorten & Interfaces SmartCard slot Yes (S/2 poorten) 2 Design Rack-montage Yes Energie Afvoer voltage 180-240 VAC Certificering cULus 60950, TAA
---	--	--	--	--	--

WEEERoHS compliance YesVeiligheid EKI-ITB 2000, ISO 9241-3/-8

Gewicht en omvang

Breedte 46 mmDiepte 180 mmHoogte 201 mmGewicht * 3,6 kgInhoud van de
verpakkingAfstandsbediening Yes

Overige specificaties

Netwerkfuncties Fast Ethernet, WLANSoort voeding AC/DC (inclusief)Grafische adapter-familie

VIAAfmetingen (BxDxH) 46 x 180 x 201 mmAudio-uitgang Yes

Genoemde prijs is exclusief btw en verzenden !!

Ook te bestellen in onze webshop mkh-electronics.store !!

8 stuks op!!