

Thomson Speedtouch ST546v6 Router Modem 4poorts Annex A ADSL (34,95 EUR)



Locatie **Noord-Holland, Amsterdam**
<https://www.advertentiex.nl/x-832148-z>

ST546v6

Speedtouch 546 ADSL-2+ modemScherpe prijs/kwaliteit modem voor de consument! (4 poort switch/Analoog) Schaf nu direct deze scherp geprijsde modem/router van Speedtouch aan en vervang uw huidige modem/router. Een consumentenoplossing voor de scherpste prijs!

De SpeedTouch 546 maakt een internetverbinding delen met meerdere PC's zeer eenvoudig, is gecertificeerd voor alle ADSL, ADSL2 en ADSL2+ netwerken in Nederland en het ideale modem voor de residentiële gebruiker. Deze ADSL2+ modem (over een analoge telefoonlijn) kan ongeëvenaarde snelheden halen. De ingebouwde snelle en zeer uitgebreide router beschikt tevens over een solide firewall.

Deze modem/router beschikt tevens over een 4 poorts switch zodat er tot 4 computers op kunnen worden aangesloten.

Technische Specificaties

Hardware specificaties

Interfaces:

- LAN:

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

10/100Base-T (RJ45)

MDI/MDI-x autosensing

10/100Base-T (RJ45)

ADSL2: Annex A
ADSL2+: Annex A

Multi-user Router

ATM-Extensive multi PVC

- ATM Quality of Service (UBR, CBR, VBR-rt, VBR-nrt)

- DSLForum TR-37 autoconfiguration

Bridging-self learning bridge at wire speed

IP Routing

- UPnP* certified Internet Gateway Device, enabling major conferencing and gaming technologies

- IPsec passthrough from multiple LAN clients, enabling secure homeworking

- Supports PPPoE, PPPoA, IPoA, CIP, ETHoA-DNS server and relay, DHCP server and relay

- Network Address Translation for connection sharing, including support for SIP, H.323,

Realaudio, FTP, irc, IKE, IPsec-ESP, Jabber, ILS,...

- Simultaneous bridging and routing of PPPoE connections, enabling network based VPNs

Management

OS independent

Easy set-up wizard

Advanced Management via telnet, HTTP, SNMP, event log

Integrated firewall

Easy SW upgrade wizard

Included

ADSL Gateway

Ethernet cable (RJ45)

Telephone cable (RJ11)

Cable filter (optional)

Power adapter

Safety leaflet