
Operating Temperature:
0° to 40°C (32° to 104°F)
Storage Temperature:
-20° to 70°C (-4° to 158°F)
Operating Humidity:
10% to 85% non-condensing
Storage Humidity:
10% to 90% non-condensing
Mounting: Ceiling Wall
Security Features: Multiple SSIDs (16) SSID Broadcast SSID to VLAN Mapping Wi-Fi Protected Access
(WPA/WPA Mixed, WPA2) Personal and Enterprise RADIUS IP and Mac-Based Access Control Rogue AP
Detection 802.1X Supplicant Channel Isolation
Security Lock:
Kensington Security Lock
Quality Of Service: WMM Bandwidth Management Client QoS DiffServ Policy (IPv4 and IPv6)
Management Interface: HTTP HTTPS SNMP
Regulatory Compliance:
FCC, CE, IC
Advanced Features: Wireless Distribution System (WDS) Workgroup Bridge IGMP/MLD
Snooping Scheduler Band Steering IPv6 Interface Link Aggregation Dual Image Support Captive
Portal Clustering
Event Notification:
Local Log, Remote Syslog, and Email Alerts
Network Diagnostics:
Log, Ping and Packet Capture
Warranty and Support:
Limited Lifetime Warranty
Centralized Management System:
Single Point Control: